Copyright[©] 2005 by Big Bike Parts, Inc.[™] No part of this instruction sheet may be reproduced without the written permission of Big Bike Parts, Inc. $^{\text{TM}}$

BIG BIKE PARTS[®] INSTALLATION INSTRUCTIONS

Brake & Clutch Lever Part No. 18-111 18-112

Fits Honda GL1800 Goldwing

WHEN INSTALLING BRAKE & CLUTCH LEVERS THERE ARE IMPORTANT FEATURES TO BE CHECKED BEFORE USE.

- I EVERS SHOULD BE ABLE TO BE ENGAGED AND DIS-ENGAGED FREELY. 1
- 2 MOST LEVERS WHEN ENGAGED & DIS-ENGAGED ACTIVATE SWITCHES. VERIFY THIS BY LISTENING FOR THE SWITCH "CLICK" NOISE WHEN ENGAGING & DIS-ENGAGED. MAKE SURE THE SWITCHES ARE WORKING BEFORE USE.
- 3. THESE LEVERS ARE ADJUSTABLE TO ADJUST THE AMOUNT OF THROW OR THE RESTING POSITION OF THE LEVER. PUSH THE LEVER FORWARD AND TURN THE DIAL. POSITION 1 IS FURTHER FROM THE GRIP THEN POSITION 5.