

Copyright© 2001 by Big Bike Parts, Inc. No part of this instruction sheet may be reproduced without the written permission of Big Bike Parts Inc.®

CruisWing Oversized
Kickstand

Part No. 52-548A

Fits GL1800 2001-2010

Revised 8/19/09

TOOLS REQUIRED: 8MM WRENCH
14MM WRENCH & SOCKET

1. PLACE MOTORCYCLE ON CENTER STAND.
2. USING 8MM WRENCH REMOVE BOLT (1A) HOLDING KICKSTAND SWITCH (1B) TO KICKSTAND (1F).
3. USING 14MM WRENCH AND SOCKET REMOVE THE SPECIAL BOLT (1C) AND NUT (1D).
4. PULL KICKSTAND (1F) TOWARD BACK OF BIKE TO RELEASE SPRING (1E).
5. REINSTALL NEW KICKSTAND (1F) IN REVERSE ORDER OF REMOVAL. BE SURE TO USE NEW SPRING PROVIDED.

NOTE: MAY NEED TO PRY KICKSTAND INTO PLACE DUE TO TIGHTNESS OF SPRING.

CAUTION: BIKE SHOULD ALWAYS BE PARKED ON A FLAT SURFACE, IF BIKE IS PARKED AT AN INCLINE THE FRONT WHEEL MUST BE POSITIONED UPHILL AS WELL AS THE RIGHT SIDE OF THE MOTORCYCLE TO PREVENT ANY ROLL OFF. BIKE SHOULD ALSO BE IN GEAR, ACCORDING TO YOUR OWNER'S MANUAL.

