



**SLOTTED SHIFT LEVER 1065**

**FITS: FRONT OR REAR STOCK REPLACEMENT ON ALL '83-UP FLT (DRESSERS AND ROAD KINGS) AND ALL '87-UP FLST MODELS.**

**PARTS INCLUDED**

- 1 Slotted Shift Lever
- 1 5/16" Hot Spot
- 1 5/16-18 x 3/4" Socket Head Cap Screw (SHCS)
- 1 Installation Instructions

*Please read and understand entire instructions before starting installation.*

**THANK YOU FOR CHOOSING KÜRYAKYN!**

**IN ORDER TO PROTECT YOU AND OTHERS FROM POSSIBLE INJURY AND/OR PROPERTY DAMAGE OR LOSS, PLEASE PAY CLOSE ATTENTION TO ALL INSTRUCTIONS, WARNINGS, CAUTIONS AND ATTENTION NOTES REGARDING THE USE AND CARE OF THIS PRODUCT.**

**WARNING!** THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN CAN RESULT IN POTENTIAL DEATH OR SERIOUS INJURY.

**CAUTION!** This indication alerts you to the fact that ignoring the contents described herein can result in potential injury or material damage.

**ATTENTION!** This indication alerts you to the fact that ignoring the contents described herein may negatively affect product performance and functionality.

**TOOLS SUGGESTED**

Set of hex wrenches, large standard screwdriver.

**STRICTLY OBSERVE THE FOLLOWING GUIDELINES IN ORDER TO USE THE PRODUCT PROPERLY AND AVOID POTENTIALLY DANGEROUS ACCIDENTS.**

**PROCEDURE**

This lever is quite versatile and can be used to replace either the stock front or stock rear shift lever or both. It can also be used in conjunction with any of our Heel Shift Eliminators if "toe only" shifting is desired.

**STEP 1** Read and understand all steps in the instructions before starting the installation. Park the motorcycle on a hard, level surface; turn off the ignition and allow the engine to cool.

**WARNING!** YOU WILL BE WORKING AROUND THE ENGINE AND EXHAUST SYSTEM DURING INSTALLATION. ENSURE THAT THE ENGINE AND EXHAUST SYSTEM HAVE FULLY COOLED TO PREVENT INJURY.

**STEP 2** Use the 3/16" Hex Key to remove the pinch bolt from the stock shift lever.

**-cont.-**

**CUSTOMER SERVICE**  
877.370.3604 (toll free)

**INSTALLATION QUESTIONS**  
techsupport@kuryakyn.com  
or call 715.247.2983

**LIMITED WARRANTY**  
Kuryakyn warrants that any Kuryakyn products sold hereunder, shall be free of defects in materials and workmanship for a period of one (1) year from the date of purchase by the consumer excepting the following provisions:

- Kuryakyn shall have no obligation in the event the customer is unable to provide a receipt showing the date the customer purchased the product(s).
- The product must be properly installed, maintained and operated under normal conditions.
- Kuryakyn makes no warranty, expressed or implied, with respect to any gold plated products.
- Kuryakyn shall not be liable for any consequential and incidental damages, including labor and paint, resulting from failure of a Kuryakyn product, failure to deliver, delay in delivery, delivery in non-conforming condition, or for any breach of contract or duty between Kuryakyn and a customer.
- Kuryakyn products are often intended for use in specific applications. Kuryakyn makes no warranty if a Kuryakyn product is used in applications other than intended.
- Kuryakyn electrical products are warranted for one (1) year from the date of purchase by the consumer. Components of Kuryakyn products containing L.E.D.s will be warranted for defects in materials and workmanship for 3 years from the date of purchase.
- Kuryakyn makes no warranty of any kind in regard to other manufacturer's products distributed by Kuryakyn. Kuryakyn will pass on all warranties made by the manufacturer and where possible, will expedite the claim on behalf of the customer, but ultimately, responsibility for disposition of the warranty claim lies with the manufacturer.

**ABOUT OUR CATALOG**

You'll find all our innovations for H-D, GL and Metric Cruisers in our annual catalogs. Order online today—select the "CATALOGS" icon. Each Kuryakyn® product comes with a Proof-of-Purchase good for a complimentary catalog. Details in packaging.

Be sure to ask your local dealer about other Kuryakyn® products, the motorcycle parts and accessories designed for riders by riders.

©2005 Kuryakyn USA® All Rights reserved.



**STEP 3** Make a mental note or measure the height of the stock lever to assist in positioning the new lever. Remove the stock lever from the splined shaft. It is sometimes helpful to use a large screwdriver to gently spread the lever to get it off the shaft.

**STEP 4** Install a shift peg on the Slotted Shift Lever. It will accept any stock H-D shift peg or equivalent.

**HELPFUL HINT**

*If re-using the stock shift peg, heating the exposed end of the stud with a small torch (i.e. Bernz-o-Matic) will break the thread locker bond and make removing the shift peg from the stock lever much easier.*

**STEP 5** Remove the pinch bolt from the Slotted Shift Lever and slide it onto the splined shaft. Sit on the bike and test the position of the lever. Make coarse adjustments by moving the lever up or down, one spline at a time. For now, don't worry if the position is not perfect.

**STEP 6** Insert the pinch bolt and tighten securely. Test the position of the lever. If it is not quite right, make fine adjustments by shortening or lengthening the shift linkage.

**CAUTION!** Ensure that the installation of this product does not interfere with the proper operation of the motorcycle before riding.

**ATTENTION!** It is the installer's responsibility to ensure that all of the fasteners (including pre-assembled) are tightened before operation of the motorcycle. Kuryakyn will not warranty components lost due to improper installation. Periodic maintenance may be required.

*Ride On!*

**Kuryakyn®**

PAGE

**2**

**SLOTTED SHIFT LEVER**

**INSTALLATION**