

INSTALLATION

SPEEDOMETER/TACH VISOR

4015

FITS:HONDA VTX 1800C, 1100 SABRE/SPIRIT/ACE/AERO, 750 MAGNA/ACE, YAMAHA V-MAX, V-STAR 1100/650, KAWASAKI MEAN STREAK, VULCAN 500/800

PART#	INCLUDED
404015	1 Chrome Visor
404015A	4 Adhesive Strips
304015	1 Instruction Sheet

TOOLS SUGGESTED

Alcohol, Clean rag

PROCEDURE AVERAGE TIME: 5 MINUTES **STEP 1** Clean the rim of the speedometer or tach with alcohol and let dry.

STEP 2 Remove the backing from the adhesive strips.

STEP 3 Position the visor on the instrument (without contact), then set it into place — apply firm pressure for about 30 seconds to insure a good bond.

Ride On!

E-MAIL

techsupport@kuryakyn.com or call 715.247.2983

WARRANTY

Küryakyn" warrants that any Küryakyn product sold hereunder, if properly installed, maintained and operated under normal conditions, shall be free from any defects in materials and workmanship for a period of one (1) year from the date the Küryakyn products are sold to the customer.

> CONSEQUENTIAL DAMAGES: Küryakyn shall not be liable for any consequential or incidental damages.

ABOUT OUR CATALOG

You'll find all our innovations for H-D, GL and Metric Cruisers in our annual catalogs. Order online today-select the "CATALOGS" icon. Each Küryakyn" product comes with a Proof-of-Purchase good for a complimentary catalog. Details in packaging.

> Be sure to ask your local dealer about other Küryakyn products, the motorcycle parts and accessories designed for riders by riders.

@2003 Küryakyn USA $^{^{\mathrm{M}}}$ All Rights reserved.

