



INSTALLATION

LED REAR TURN SIGNAL INSERTS

4826

PARTS INCLUDED

- 2 3-1/4" LED Replacement Lenses — Smoke
- 1 Load Equalizer
- 1 Dielectric Grease
- 3 Wire Connectors—(Scotch Locks)
- 1 Installation Instructions

Please read and understand entire instructions before starting installation.

THANK YOU FOR CHOOSING KÜRYAKYN!

IN ORDER TO PROTECT YOU AND OTHERS FROM POSSIBLE INJURY AND/OR PROPERTY DAMAGE OR LOSS, PLEASE PAY CLOSE ATTENTION TO ALL INSTRUCTIONS, WARNINGS, CAUTIONS AND ATTENTION NOTES REGARDING THE USE AND CARE OF THIS PRODUCT.

CAUTION! This indication alerts you to the fact that ignoring the contents described herein can result in potential injury or material damage.

TOOLS SUGGESTED

Phillips screwdriver

STRICTLY OBSERVE THE FOLLOWING GUIDELINES IN ORDER TO USE THE PRODUCT PROPERLY AND AVOID POTENTIALLY DANGEROUS ACCIDENTS.

STEP 1 Read and understand all steps in the instructions before starting the installation. Park the motorcycle on a hard, level surface and turn off the ignition.

STEP 2 Remove the lenses from the stock turn signal fixtures. The screws will be re-used.

STEP 3 Remove the stock turn signal bulb from the fixtures by pushing the bulb slightly inward and turning counter clockwise.

CAUTION! LED circuit boards are polarity sensitive! Use a test light to check the polarity of the bike's wiring before connecting the LED circuit board. Kuryakyn is not responsible for damage to the LED circuit board caused by reversed polarity.

CAUTION! Use a test light to verify wire functions before connecting the LED circuit board to non-stock wiring. Kuryakyn is not responsible for damage to the LED circuit board caused by non-stock wiring

STEP 4 Plug the LED Lens connector into the bulb socket in the reverse manner of removing the stock bulb.

4826-23HD-0111

-cont.-



CUSTOMER SERVICE

877.370.3604 (toll free)

INSTALLATION QUESTIONS

techsupport@kuryakyn.com
or call 715.247.2983

LIMITED WARRANTY

Kuryakyn warrants that any Kuryakyn products sold hereunder, shall be free of defects in materials and workmanship for a period of one (1) year from the date of purchase by the consumer excepting the following provisions:

- Kuryakyn shall have no obligation in the event the customer is unable to provide a receipt showing the date the customer purchased the product(s).
 - The product must be properly installed, maintained and operated under normal conditions.
 - Kuryakyn makes no warranty, expressed or implied, with respect to any gold plated products.
 - Kuryakyn shall not be liable for any consequential and incidental damages, including labor and paint, resulting from failure of a Kuryakyn product, failure to deliver, delay in delivery, delivery in nonconforming condition, or for any breach of contract or duty between Kuryakyn and a customer.
- Kuryakyn products are often intended for use in specific applications. Kuryakyn makes no warranty if a Kuryakyn product is used in applications other than intended.
- Kuryakyn electrical products are warranted for one (1) year from the date of purchase by the consumer. L.E.D.'S contained in components of Kuryakyn products will be warranted for defects in materials and workmanship for 3 years from the date of purchase where as all other components shall be warranted for one(1) year. This includes, but is not limited to; control modules, wiring, chrome & other components.

• Kuryakyn makes no warranty of any kind in regard to other manufacturer's products distributed by Kuryakyn. Kuryakyn will pass on all warranties made by the manufacturer and where possible, will expedite the claim on behalf of the customer, but ultimately, responsibility for disposition of the warranty claim lies with the manufacturer.

ABOUT OUR CATALOG

For purchasing Kuryakyn® products, you can receive a complete catalog free of charge. Send the Proof-of-Purchase below with your address to: Kuryakyn, P.O. Box 339, Somerset, WI 54025. Please indicate either Accessories Catalog for Harley-Davidson® or GL & Metric Cruisers.

Be sure to ask your local dealer about other Kuryakyn® products, the motorcycle parts and accessories designed for riders.

©2005 Kuryakyn USA® All Rights reserved.



kuryakyn.com

STEP 5 Attach the LED Lenses to the light fixtures using the stock screws. Tighten the screws to snug — do not over tighten.

STEP 6 If the turn signals light but do not flash, or flash normally for four or five times then go into a rapid flash mode, or if the security system warning light in the dash is lit, an additional load equalizer (included) is needed. For easiest installation, splice it into the main lighting wire harness under the seat using the included clip type splices. The equalizer will have two purple wires, and one black wire. The purple wires are turn signal positive wires; they are not side specific. The black wire is ground. Connect one each of the equalizers violet wires to the left and right turn signal wires on the bikes lighting harness. Connect the black wire from the equalizer to a ground wire on the bikes harness. If the bike is equipped with a Panacea taillight system, or a Run-Turn-Brake controller, plug the load equalizer into the unused pigtail on the controller or splice the additional load equalizer on to the similar colored wires of the equalizer already in use.

CAUTION! Always install the load equalizer upstream of any existing after market multifunction control modules . Do not install a load equalizer between a module and the turn signals as this will overload the module . Overloading will damage the module and create a fire hazard !

CAUTION! Load equalizers generate heat when in use . Avoid using the turn signals for an extended period of time, otherwise the load equalizer will over heat. Never operate the four-way flashers unless you first remove the load equalizer . Over heating damages the load equalizer causing loss of turn signal operation and could create a fire hazard !

CAUTION! Do not secure the load equalizer to the control module ! Excess heat from the load equalizer could damage the control module .

Ride On!