

## INSTALLATION INSTRUCTIONS

# MID-FRAME COVERS, '14-UP TOURING & TRIKE

6997

### THANK YOU FOR CHOOSING KURYAKYN!

Protect yourself and others from possible injury and property damage or loss. Pay close attention to all instructions, warnings, cautions, and notices regarding the installation, use, and care of this product.

**▲** WARNING

THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN CAN RESULT IN POTENTIAL DEATH OR SERIOUS INJURY.

A CAUTION

THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN CAN RESULT IN MINOR OR MODERATE POTENTIAL INJURY.

NOTICE

THIS INDICATION AFFRES YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN MAY NEGATIVELY AFFECT PRODUCT PERFORMANCE AND FUNCTIONALITY OR DAMAGE THE PRODUCT ITSELF OR THE PRODUCT TO WHICH IT IS BEING ATTACHED.

### ENSURE THAT THE FOLLOWING PARTS HAVE BEEN INCLUDED IN THE KIT:

- Right Hand Upper Mid Frame Cover
- 1 Right Hand Lower Mid Frame Cover
- 1 Left Hand Upper Mid Frame Cover
- Left Hand Lower Mid Frame Cover
- Hardware Kit, containing
  - 2 Grommet Side Cover
  - 4 Spacer
  - 2 Alcohol Pad
  - 4 8" Black Cable Ties

### YOU WILL ALSO NEED:

Set of Hex Wrenches, Combination Wrenches, Socket Set and Ratchet

NOTICE

THESE INSTALLATION INSTRUCTIONS CONTAIN IMPORTANT INFORMATION. ENSURE THE END USER RECEIVES THIS COPY AND IS AWARE OF ITS IMPORTANCE FOR FUTURE USE.

STEP 1

Read and understand all steps in the instructions before starting the installation. Park the motorcycle on a hard, level surface and turn off the ignition. Let motorcycle cool.

**▲** WARNING

YOU WILL BE WORKING AROUND THE ENGINE AND EXHAUST SYSTEM DURING INSTALLATION. ENSURE THAT THE ENGINE AND EXHAUST SYSTEM HAVE FULLY COOLED TO PREVENT INJURY.

STEP 2 Remove motorcycle seat.

STEP 3 Remove the left and right saddlebags, and set them on a soft, clean and stable surface.

STEP 4 Remove both the left and right side-covers.

> Note: If your bike is equipped with H-D Mid Frame Air Deflectors, remove them now and save all hardware for reinstallation.

STEP 5 Remove the left and right passenger floorboard/peg mounts from frame and set aside for reinstallation.

NOTICE

ENSURE PROPER ADHESION OF THIS PRODUCT. REMOVE ALL GREASE, OIL, BUGS, DIRT, AND OTHER DEBRIS (INCLUDING WAX AND POLISH) FROM THE INSTALLATION AREA. KURYAKYN WILL NOT PROVIDE WARRANTY COVERAGE ON PRODUCTS OR COMPONENTS LOST OR DAMAGED DUE TO IMPROPER INSTALLATION.

DO NOT ATTEMPT THIS INSTALLATION IN TEMPERATURES BELOW 50°F (10°C). PROPER ADHESIVE BONDING ONLY OCCURS ABOVE 50°F (10°C).



KURYAKYN.COM

866 277 9598 | INFO@KURYAKYN.COM 454 COUNTY ROAD VV SOMERSET, WI 54025











## **INSTALLATION INSTRUCTIONS**

# MID-FRAME COVERS, '14-UP TOURING & TRIKE

6997

#### -CONTINUED-

- STEP 6 Refer to PIC 1. Using warm soapy water and a clean rag, remove all dirt and debris from the installation area; allow the area to dry completely. Wipe the installation area with the included alcohol pad to remove any wax or polish; allow the area to dry completely.
- STEP 7 Refer to PIC 2. Take the lower right mid-frame cover and dry fit it to the bike. Make any temporary light marks to make sure that you have something that you will be able to lineup with when you apply the cover to your bike.
- STEP 8 Use your fingernail to rub the adhesive backing on the lower mid-frame; this will activate the adhesive. Remove and discard the backing.
- STEP 9 Refer to PIC 2 and 3. Line up the holes for the rear floorboard mount and any mark that was made and press firmlyinto place. Make sure you apply even pressure to achieve full contact to the frame. If needed, you can place the rear passenger board mount back on and tighten.
- **STEP 10** Refer to PIC 4. Once the lower mid-frame is in place, dry fit the upper cover to find the best fitting location.

Note: The upper cover will over lap the bottom cover.

- **STEP 11** Use your fingernail to rub the adhesive backing on the upper midframe; this will activate the adhesive. Remove and discard the backing.
- Refer to PIC 4 and 5. Place the upper cover on the frame; be sure to **STEP 12** press firmly to ensure that the entire adhesive has made contact with the frame.
- **STEP 13** Replace the front grommet for the side cover with the new supplied grommet. This allows proper clearance for the side cover to clear the new mid-frame covers.
- **STEP 14** Repeat steps 6 through 13 on the left hand side.
- **STEP 15** If applicable, replace the H-D Mid Frame Air Deflectors removed previously. The four(4) included spacers are to be used between the Air Deflectors and the frame. Tighten with the stockhardware.
- **STEP 16** When all the mid-frame covers are on the bike, you can reinstall the side covers, the saddlebags, and the seat.









### KURYAKYN.COM

866 277 9598 | INFO@KURYAKYN.COM 454 COUNTY ROAD VV SOMERSET, WI 54025











### INSTALLATION INSTRUCTIONS

## MID-FRAME COVERS, '14-UP TOURING & TRIKE

6997

-CONTINUED-

**NOTICE** 

IT IS THE INSTALLER'S RESPONSIBILITY TO ENSURE THAT ALL OF THE FASTENERS (INCLUDING PRE-ASSEMBLED) ARE TIGHTENED BEFORE OPERATION OF THE MOTORCYCLE. KURYAKYN WILL NOT PROVIDE WARRANTY COVERAGE ON PRODUCTS OR COMPONENTS LOST DUE TO IMPROPER INSTALLATION OR LACK OF MAINTENANCE. PERIODIC INSPECTION AND MAINTENANCE ARE REQUIRED ON ALL FASTENERS.



#### LIMITED WARRANTY

Kuryakyn warrants that any Kuryakyn products sold hereunder, shall be free of defects in materials & workmanship for a period of one (1) year from the date of purchase by the consumer excepting the following provisions:

- 1. Kuryakyn shall have no obligation in the event the customer is unable to provide a receipt showing the date the customer purchased the product(s).
- 2. The product must be properly installed, maintained & operated under normal conditions.
- 3. Kuryakyn shall not be liable for any consequential & incidental damages, including labor & paint, resulting from failure of a Kuryakyn product, failure to deliver, delay in delivery, delivery in nonconforming condition, or for any breach of contract or duty between Kuryakyn & a customer.
- 4. Kuryakyn products are often intended for use in specific applications. Kuryakyn makes no warranty if a Kuryakyn product is used in applications other than intended.
- 5. Kuryakyn electrical products are warranted for one (1) year from the date of purchase by the consumer. L.E.D.'s contained in components of Kuryakyn products will be warranted for defects in materials & workmanship for 3 years from the date of purchase whereas all other components shall be warranted for one (1) year.
- 6. All warranty claims must be directed to the place of purchase. Merchandise sold through internet auction sites or any other unauthorized reseller shall not carry a Kuryakyn warranty. If unsure, please contact the place of purchase to verify they are an authorized Kuryakyn reseller.

### RETURN POLICY

Merchandise determined to be defective may be returned up to one year from the date of purchase. Returns must be processed through original seller. Returned merchandise for any other reason other than warranty claims must be in like new condition & subject to a 20% restocking fee. All returns are subject to inspection for determination of full or partial credit. Any returned part that shows evidence of being used or installed contrary to manufacturer's instructions, &/or subjected to improper handling, packaging or return shipping by the customer, will not be eligible for exchange, refund or warranty consideration. All returned electrical items will be inspected & tested. If electrical item is deemed functional, no credit will be issued & item will be returned. All sales are final on discontinued or closeout merchandise.

#### ©2015 KURYAKYN HOLDINGS, LLC ALL RIGHTS RESERVED

KURYAKYN, KURYAKYN K logo and the marks appearing on this instruction sheet are registered and common law trademarks of Kuryakyn Holdings except noted third-party trademarks. A full listing of trademarks and trademark registrations owned by Kurvakyn Holdings can be found at www.kurvakyn.com/legal-notice.

Emissions Notice: The California Air Resources Board (CARB) does not permit the use of aftermarket emission-related parts (s) that after the performance of OFM emission-related devices unless CARB has issued an Executive Order, other than on racing vehicles on closed courses. Check your local laws and manufacturer's information.

Listed Manufacturers and product model names are for reference only. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. All specifications are subject to change without notice.

For additional information on third-party product and company names, please consult our Web page at www.kuryakyn.com/legal-notice

KURYAKYN.COM





