

INSTALLATION

PREMIER LUGGAGE RACK

7156

FITS: FOR H-D: ALL KURYAKYN BACKRESTS (EXCEPT TRANSFORMER P/N 1606), ALL '84-'09 SOFTAIL MODELS (EX. '00-'07 FXSTD AND '06-'08 FXST, FXSTB AND FXSTS AND '07-'08 FLSTF, FXSTC) WITH STOCK OR ACCESSORY H-D RIGID OR DETACHABLE SIDE PLATES. ALL '91-'09 DYNA MODELS WITH SISSY BAR UPRIGHTS MOUNTED ON H-D RIGID OR DETACHABLE SIDE PLATES. ALL '82-'09 SPORTSTER MODELS WITH SISSY BAR UPRIGHTS MOUNTED ON H-D RIGID OR DETACHABLE SIDE PLATES (DOES NOT WORK WITH BAGGERS OR OTHERS MODELS THAT HAVE QUICK DETACH KITS WITH SINGLE PIECE BACKRESTS/SIDE STRAPS.)

FOR METRIC, H-D AND UNIVERSAL APPLICATIONS:

EXISTING BACKREST, ALL KURYAKYN BACKRESTS (EXCEPT TRANSFORMER BACKRESTS P/N 1606) AND ADJUSTABLE FOR UNIVERSAL APPLICATIONS FOR INSTALLATION ON THE MOUNTING BOLT SIDE OF THE SIDE STRAPS WITH THE FOLLOWING DIMENSIONS.

SISSY BAR REQUIRES MOUNTING BOLTS TO BE 1/4 – 20 WITH 1-3/16" TO 1-5/16 CENTER TO CENTER SPACING MOUNTING INSIDE EXISTING SIDE STRAPS WITH WIDTH FROM (5-5/8" TO 6") OR (7-1/4" TO 7-1/2") WIDE. MOUNTING OUTSIDE EXISTING SIDE STRAPS WITH WIDTH FROM (5-3/8" TO 5-5/8") OR (7" TO 7-1/4") WIDE.

PARTS INCLUDED

- 1 Luggage Rack
- 2 Luggage Rack Mounts
- 1 Hardware Kit Including:
 - 4 #10 Flat Washers
 - 4 10-24 x 1/2 Button Head Cap Screw
 - 4 1/4-20 x 3/4 Button Head Cap Screw
- 1 Installation Instructions

TOOLS SUGGESTED

Set of hex wrenches

STRICTLY OBSERVE THE FOLLOWING GUIDELINES IN ORDER TO USE THE PRODUCT PROPERLY AND AVOID POTENTIALLY DANGEROUS ACCIDENTS.

Please read and understand entire instructions before starting installation.

THANK YOU FOR CHOOSING KÜRYAKYN!

IN ORDER TO PROTECT YOU AND OTHERS FROM POSSIBLE INJURY AND/OR PROPERTY DAMAGE OR LOSS, PLEASE PAY CLOSE ATTENTION TO ALL INSTRUCTIONS, WARNINGS, CAUTIONS AND ATTENTION NOTES REGARDING THE USE AND CARE OF THIS PRODUCT.

WARNING! THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE

CONTENTS DESCRIBED HEREIN CAN RESULT IN POTENTIAL DEATH OR

SERIOUS INJURY.

CAUTION! This indication alerts you to the fact that ignoring the contents described herein

can result in potential injury or material damage.

ATTENTION! This indication alerts you to the fact that ignoring the contents described herein

may negatively affect product performance and functionality.

077.370.3004 (toll fict

CUSTOMER SERVICE 877.370.3604 (toll free)

INSTALLATION QUESTIONS

techsupport@kuryakyn.com or call 715.247.2983

LIMITED WARRANTY

Küryakyn warrants that any Küryakyn products sold hereunder, shall be free of defects in materials and workmanship for a period of one (1) year from the date of purchase by the consumer excepting the following provisions:

- Küryakyn shall have no obligation in the event the customer is unable to provide a receipt showing the date the customer purchased the product(s).
 - The product must be properly installed, aintained and operated under normal conditions.
- Küryakyn makes no warranty, expressed or implied, with respect to any gold plated products.
- Küryakyn shall not be liable for any consequential and incidental damages, including labor and paint, resulting from failure of a Küryakyn product, failure to deliver, delay in delivery, delivery in nonconforming condition, or for any breech of contract or duty between Küryakyn and a customer.
 - Küryakyn products are often intended for use in specific applications. Küryakyn makes no warranty if a Küryakyn product is used in applications other than intended.
- Küryakyn electrical products are warranted for one (1) year from the date of purchase by the consumer. Components of Küryakyn products containing L.E.D.s will be warranted for defects in materials and workmanship for 3 years from the date of purchase.
- Küryakyn makes no warranty of any kind in regard to other manufacturer's products distributed by Küryakyn. Küryakyn will pass on all warranties made by the manufacturer and where possible, will expedite the claim on behalf of the customer, but ultimately, responsibility for disposition of the warranty claim lies with the manufacturer.

ABOUT OUR CATALOG

You'll find all our innovations for H-D, GL and Metric Cruisers in our annual catalogs. Order online today-select the "CATALOGS" icon. Each Küryakyn® product comes with a Proof-of-Purchase good for a complimentary catalog. Details in packaging.

Be sure to ask your local dealer about other Küryakyn® products, the motorcycle parts and accessories designed for riders by riders.

©2005 Küryakyn USA® All Rights reserved.




-cont.-

PROCEDURE

STEP 1 Read and understand all steps in the instructions before starting the installation. Park the motorcycle on a hard, level surface and turn off the ignition.



- **STEP 2** Loosely connect the mounting brackets to the bottom of the luggage rack.
- **STEP 3** Remove the four screws that secure the sissy bar to the side plates.
- **STEP 4** Install the provided 1/4-20 x 3/4 Button Head Cap Screw to secure the luggage rack mounting brackets to the sissy bar side plates.
- **STEP 5** Once the mounting brackets are secured to the sissy bar side plates, you can align the luggage rack and tighten up all the hardware.



ATTENTION! Side plates have two different ways to mount to the luggage rack. If your sissy bar is narrow, you will need to mount the side plates with the rolled edge to the outside. If your sissy bar is wide, you will need to mount the rolled edge to the inside of the luggage rack. (PIC 1 for wide application.)

Ride On!



Küryakyn