



BEAR CLAW MIRROR ACCENTS 7324

FITS: ALL '01-UP GL1800

PARTS INCLUDED

- 1 Pair Bear Claw Mirror Accents
- 1 Alcohol Pad
- 1 Installation Instructions

Please read and understand entire instructions before starting installation.

THANK YOU FOR CHOOSING KÜRYAKYN!

IN ORDER TO PROTECT YOU AND OTHERS FROM POSSIBLE INJURY AND/OR PROPERTY DAMAGE OR LOSS, PLEASE PAY CLOSE ATTENTION TO ALL INSTRUCTIONS, WARNINGS, CAUTIONS AND ATTENTION NOTES REGARDING THE USE AND CARE OF THIS PRODUCT.

CAUTION! This indication alerts you to the fact that ignoring the contents described herein can result in potential injury or material damage.

ATTENTION! This indication alerts you to the fact that ignoring the contents described herein may negatively affect product performance and functionality.

TOOLS SUGGESTED

Soapy water, clean rag and low-tack masking tape

STRICTLY OBSERVE THE FOLLOWING GUIDELINES IN ORDER TO USE THE PRODUCT PROPERLY AND AVOID POTENTIALLY DANGEROUS ACCIDENTS.

PROCEDURE

STEP 1 Clean the mounting locations thoroughly with soapy water and a clean rag.

STEP 2 Clean the mounting locations with the included alcohol pad and allow to dry completely.


ATTENTION! Be sure the areas are free of grease, oil, dirt or other debris to ensure proper adhesion. Kuryakyn WILL NOT warranty any parts lost due to improper installation.

STEP 3 Dry fit the Bear Claw Mirror Accent and use low tack masking tape to mark the location on the mirror housing. See PIC.1.

ATTENTION! The adhesive may not correctly bond if applied at temperatures less than 50° F. Do not attempt this installation in temperatures less than 50° F.

-cont.-

MARK INSTALLATION LOCATION WITH LOW-TACK TAPE



CUSTOMER SERVICE
877.370.3604 (toll free)

INSTALLATION QUESTIONS
techsupport@kuryakyn.com
or call 715.247.2983

LIMITED WARRANTY
Kuryakyn warrants that any Kuryakyn products sold hereunder, shall be free of defects in materials and workmanship for a period of one (1) year from the date of purchase by the consumer excepting the following provisions:

- Kuryakyn shall have no obligation in the event the customer is unable to provide a receipt showing the date the customer purchased the product(s).
- The product must be properly installed, maintained and operated under normal conditions.
- Kuryakyn makes no warranty, expressed or implied, with respect to any gold plated products.
- Kuryakyn shall not be liable for any consequential and incidental damages, including labor and paint, resulting from failure of a Kuryakyn product, failure to deliver, delay in delivery, delivery in nonconforming condition, or for any breach of contract or duty between Kuryakyn and a customer.
- Kuryakyn products are often intended for use in specific applications. Kuryakyn makes no warranty if a Kuryakyn product is used in applications other than intended.
- Kuryakyn electrical products are warranted for one (1) year from the date of purchase by the consumer. Components of Kuryakyn products containing L.E.D.s will be warranted for defects in materials and workmanship for 3 years from the date of purchase.
- Kuryakyn makes no warranty of any kind in regard to other manufacturer's products distributed by Kuryakyn. Kuryakyn will pass on all warranties made by the manufacturer and where possible, will expedite the claim on behalf of the customer, but ultimately, responsibility for disposition of the warranty claim lies with the manufacturer.

ABOUT OUR CATALOG

You'll find all our innovations for H-D, GL and Metric Cruisers in our annual catalogs. Order online today—select the "CATALOGS" icon. Each Kuryakyn product comes with a Proof-of-Purchase good for a complimentary catalog. Details in packaging.

Be sure to ask your local dealer about other Kuryakyn products, the motorcycle parts and accessories designed for riders by riders.

©2005 Kuryakyn USA All Rights reserved.



STEP 4 Rub the adhesive backing to activate the adhesive.

STEP 5 Remove the adhesive backing paper.

STEP 6 Position the Bear Claw Mirror Accent on the mirror housing. Press into place – see Note below. Press for 60 seconds to ensure full adhesive bond. Full bond strength will occur within 24 hours.

NOTE Press the mirror edge of the Bear Claw Mirror Accent into place first and then move outward to the edges to ensure full adhesive bond. [PIC.2](#).

NOTE The Bear Claw Mirror Accent was designed to flex and bend to follow the contour of the mirror housing. Ensure that the entire piece is pressed into place.

CAUTION! Ensure that the installation of this product does not interfere with the proper operation of the motorcycle before riding.

STEP 7 Repeat STEP 3 through STEP 6 for the opposite side.

Ride On!



PIC.2

PRESS ACCENT IN PLACE; STARTING FROM THE MIRROR EDGE THEN OUTWARD TO EDGES