



# INSTALLATION



## LED RING OF FIRE™ ROTOR LIGHTS 7403

### AMBER OUTWARD SHINING/RED AND BLUE INWARD SHINING

FITS: '88-UP GL1500

#### PARTS INCLUDED

- 1 Pair of Chrome Trim Rings with L.E.D. Lights Installed
- 1 Wiring Harness
- 8 6-32 x 9/16" Button Head Cap Screws
- 8 #6 Flat Washer (.435" O.D.)
- 8 #6 Flat Washer (.315" O.D.)
- 8 6-32 Nylon Insert Nuts
- 1 Installation Instructions

Please read and understand entire instructions before starting installation.

#### THANK YOU FOR CHOOSING KÜRYAKYN!

#### TOOLS SUGGESTED

Drill with 1/8" bit, set of wrenches, set of hex wrenches, splicing supplies, duct tape

**ATTENTION!** A factory service manual may be helpful in performing this installation. Do not attempt to perform this installation if you are not confident in your ability to complete all steps in the procedure; consult a trained technician.

**ATTENTION!** This procedure requires making permanent modifications to the Rotor Cover; this may void your warranty. Consult your dealer for more information.

**ATTENTION!** When routing the wiring harness, be sure to keep the wiring away from any moving parts. Kuryakyn **WILL NOT** warranty any electrical component that fails due to pinched, crimped, broken, abraded, or frayed wires.

**CAUTION! AVOID POTENTIAL ELECTRICAL SHOCK! BE SURE TO DISCONNECT THE BATTERY BEFORE STARTING THIS PROCEDURE.**

#### PROCEDURE

**STEP 1** Remove the stock rotor covers from the motorcycle.

**STEP 2** Lay the rotor cover on a flat surface with the shiny side up.

**STEP 3** Place a Ring of Fire trim ring around the rotor cover so the wires exit near the top of the rotor cover, as shown. See PIC.1.

-cont.-

PIC.1



#### CUSTOMER SERVICE

877.370.3604 (toll free)

#### INSTALLATION QUESTIONS

techsupport@kuryakyn.com  
or call 715.247.2983

#### LIMITED WARRANTY

Kuryakyn warrants that any Kuryakyn products sold hereunder, shall be free of defects in materials and workmanship for a period of one (1) year from the date of purchase by the consumer excepting the following provisions:

- Kuryakyn shall have no obligation in the event the customer is unable to provide a receipt showing the date the customer purchased the product(s).
- The product must be properly installed, maintained and operated under normal conditions.
- Kuryakyn makes no warranty, expressed or implied, with respect to any gold plated products.
- Kuryakyn shall not be liable for any consequential and incidental damages, including labor and paint, resulting from failure of a Kuryakyn product, failure to deliver, delay in delivery, delivery in nonconforming condition, or for any breach of contract or duty between Kuryakyn and a customer.
- Kuryakyn products are often intended for use in specific applications. Kuryakyn makes no warranty if a Kuryakyn product is used in applications other than intended.
- Kuryakyn electrical products are warranted for one (1) year from the date of purchase by the consumer. Components of Kuryakyn products containing L.E.D.s will be warranted for defects in materials and workmanship for 3 years from the date of purchase.
- Kuryakyn makes no warranty of any kind in regard to other manufacturer's products distributed by Kuryakyn. Kuryakyn will pass on all warranties made by the manufacturer and where possible, will expedite the claim on behalf of the customer, but ultimately, responsibility for disposition of the warranty claim lies with the manufacturer.

#### ABOUT OUR CATALOG

You'll find all our innovations for H-D, GL and Metric Cruisers in our annual catalogs. Order online today—select the "CATALOGS" icon. Each Kuryakyn product comes with a Proof-of-Purchase good for a complimentary catalog. Details in packaging.

Be sure to ask your local dealer about other Kuryakyn products, the motorcycle parts and accessories designed for riders by riders.

©2005 Kuryakyn USA All Rights reserved.



**STEP 4** Holding the ring firmly in position, carefully mark and drill the four mounting holes in each rotor cover. Secure the ring to each rotor cover with four (4) of the button head cap screws, large and small flat washers, and nylon insert nut. See [PIC.2](#).

**STEP 5** Using the duct tape, secure the wires to the inside of the rotor cover so they will not interfere with any moving parts. The wires should exit the cover near where the fork slider provision is in the cover.

**STEP 6** Re-install the rotor cover on the bike.

**STEP 7** Connect the ring terminals on each side to a ground. Connect the wiring harness to the pin terminals on the Ring of Fire.

**STEP 8** Neatly route the wiring harness up one (or both) of the brake lines to your choice of a switched, fused power source. Make your connection to this power source, and carefully insulate this connection.

**ATTENTION!** When routing the wiring harness, be sure to keep the wiring away from any moving parts. Küryakyn **WILL NOT** warranty any electrical component that fails due to pinched, crimped, broken, abraded, or frayed wires.

**STEP 9** Wipe off all fingerprints, smudges, etc. from the rotor cover and ring.

*Ride On!*

