



INSTALLATION

BLACK ERGO PLUS ENGINE GUARD

7576

PARTS INCLUDED

- 1 Black Ergo Plus Engine Guard Assembly for Touring
- 1 Hardware Kit Including:
 - 1 5/16" Flat Washer
 - 1 5/16"-18 x 3/4" Socket Head Cap Screw
 - 2 3/8"-16 x 1" Socket Head Cap Screws
 - 2 3/8"-16 Nylon Nuts
 - 4 3/8" Flat Washers
- 1 Installation Instructions

Please read and understand entire instructions before starting installation.

THANK YOU FOR CHOOSING KÜRYAKYN!

IN ORDER TO PROTECT YOU AND OTHERS FROM POSSIBLE INJURY AND/OR PROPERTY DAMAGE OR LOSS, PLEASE PAY CLOSE ATTENTION TO ALL INSTRUCTIONS, WARNINGS, CAUTIONS AND ATTENTION NOTES REGARDING THE USE AND CARE OF THIS PRODUCT.

WARNING! THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN CAN RESULT IN POTENTIAL DEATH OR SERIOUS INJURY.

ATTENTION! This indication alerts you to the fact that ignoring the contents described herein may negatively affect product performance and functionality.

CAUTION! This indication alerts you to the fact that ignoring the contents described herein can result in potential injury or material damage.

TOOLS SUGGESTED

Set of Hex Wrenches, Torx Wrenches, Combination Wrenches, Socket Set with Ratchet, Blue Thread Locker

STRICTLY OBSERVE THE FOLLOWING GUIDELINES IN ORDER TO USE THE PRODUCT PROPERLY AND AVOID POTENTIALLY DANGEROUS ACCIDENTS.

STEP 1 Read and understand all steps in the instructions before starting the installation. Park the motorcycle on a hard, level surface and turn off the ignition. Let cool.

NOTE: Pictures shown are of chrome parts. Installation of black parts will be the same.

WARNING! IF INSTALLING THIS PRODUCT FOR ANOTHER PARTY, PLEASE MAKE SURE THEY RECEIVE THIS COPY OF THE INSTALLATION INSTRUCTIONS SO THEY ARE AWARE OF THESE IMPORTANT WARNINGS.

WARNING! YOU WILL BE WORKING AROUND THE ENGINE AND EXHAUST SYSTEM DURING INSTALLATION. ENSURE THAT THE ENGINE AND EXHAUST SYSTEM HAVE FULLY COOLED TO PREVENT INJURY.

CUSTOMER SERVICE

877.370.3604 (toll free)

INSTALLATION QUESTIONS

techsupport@kuryakyn.com
or call 715.247.2983

LIMITED WARRANTY

Kuryakyn warrants that any Kuryakyn products sold hereunder, shall be free of defects in materials and workmanship for a period of one (1) year from the date of purchase by the consumer excepting the following provisions:

- Kuryakyn shall have no obligation in the event the customer is unable to provide a receipt showing the date the customer purchased the product(s).
 - The product must be properly installed, maintained and operated under normal conditions.
 - Kuryakyn makes no warranty, expressed or implied, with respect to any gold plated products.
 - Kuryakyn shall not be liable for any consequential and incidental damages, including labor and paint, resulting from failure of a Kuryakyn product, failure to deliver, delay in delivery, delivery in nonconforming condition, or for any breach of contract or duty between Kuryakyn and a customer.
- Kuryakyn products are often intended for use in specific applications. Kuryakyn makes no warranty if a Kuryakyn product is used in applications other than intended.
- Kuryakyn electrical products are warranted for one (1) year from the date of purchase by the consumer. L.E.D.'S contained in components of Kuryakyn products will be warranted for defects in materials and workmanship for 3 years from the date of purchase where as all other components shall be warranted for one(1) year. This includes, but is not limited to; control modules, wiring, chrome & other components.
- Kuryakyn makes no warranty of any kind in regard to other manufacturer's products distributed by Kuryakyn. Kuryakyn will pass on all warranties made by the manufacturer and where possible, will expedite the claim on behalf of the customer, but ultimately, responsibility for disposition of the warranty claim lies with the manufacturer.

ABOUT OUR CATALOG

For purchasing Kuryakyn® products, you can receive a complete catalog free of charge. Send the Proof-of-Purchase below with your address to: Kuryakyn, P.O. Box 339, Somerset, WI 54025. Please indicate either Accessories Catalog for Harley-Davidson® or GL & Metric Cruisers.

Be sure to ask your local dealer about other Kuryakyn® products, the motorcycle parts and accessories designed for riders by riders.

©2005 Kuryakyn USA® All Rights reserved.

PROOF OF PURCHASE



kuryakyn.com

WARNING! THE ERGO GUARD IS NOT DESIGNED OR INTENDED TO PROVIDE PROTECTION TO THE RIDER OR VEHICLE IN A CRASH OR COLLISION.

WARNING! THE INSTALLATION OF ERGO ENGINE GUARDS MAY AFFECT GROUND CLEARANCE WHEN CORNERING.

WARNING! IMPROPER INSTALLATION OR USE OF THIS PRODUCT COULD RESULT IN SERIOUS INJURY OR DEATH.

ATTENTION! A factory service manual may be helpful in performing this installation. Do not attempt to perform this installation if you are not confident in your ability to complete all steps in the procedure; consult a trained technician.

ATTENTION! Check clearance for proper operation of controls. Ergo guards provide additional positions to place your feet/new riding positions. Confirm clearance and relation of your feet to the shifter and brake levers.

CAUTION! Avoid damage to the motorcycle. Protect painted surfaces with a soft cloth or blanket.

STEP 2 Remove the stock engine guard; refer to your factory service manual for specific instructions.

ATTENTION! Use a drop of blue thread locker on all fasteners.

STEP 3 As shown in PIC 1, place the Ergo Guard in position and loosely secure the center mounting point using the supplied 5/16" cap screw and washer. Do not tighten the fastener at this point.

STEP 4 As shown in PIC 2 and PIC 3: **On '08-earlier models:** loosely secure both the left and right lower mounting points using the 3/8" cap screws, flat washers, and Nylock nuts. **On '09-later models:** Loosely secure both the left and right lower mounting points using the 3/8" cap screws and a flat washer on each.

STEP 5 Verify the Ergo Guard is positioned correctly, with no interference to the bike's controls. Then tighten all three fasteners to 15-20 ft/lbs.

STEP 6 The Ergo Guard has dual-position footpegs (See PIC 4); lift the footpegs and pull them away from the supports to use in the extended position. As shown in PIC 5, fold the footpegs into the cutouts on the supports to use in the retracted position.

STEP 7 To adjust the angle of the footpeg when it is extended (see PIC 6), adjust the depth of the set screw in the hinged joint. Back the screw out for a deeper angle. Apply a dab of blue LocTite to prevent the fastener from loosening.

CAUTION! Ensure that the installation of this product does not interfere with the proper operation of the motorcycle before riding.

ATTENTION! It is the installers' responsibility to make sure all fasteners (including pre-assembled) are tightened before operation of motorcycle. Küryakyn will not warranty components that are lost due to improper installation. Periodic maintenance may be required.

