



INSTALLATION

TRANSMISSION COVER

7710

PARTS INCLUDED

- 1 Chrome Cover for Left Side
- 1 Standoff Stud M10 x 1.25 x 6
- 1 Flat Washer 10.3mm I.D. x 20mm O.D.
- 1 Flange Bolt - Chrome M6 x 1.0 x 16mm
- 1 Large Chrome Cover for Right Side
- 1 Slotted Black Bracket
- 1 Right Angle Black Bracket
- 3 Flat Washer - Black Plastic 8mm I.D. x 1/2" O.D.
- 1 Waisted Flange Bolt M8 x 1.25 x 27mm
- 1 Threaded Spacer 14mm O.D. x 11mm
- 1 Flange Bolt M8 x 1.25 x 16mm
- 1 Socket Head Cap Screw M8 x 1.25 x 12mm
- 1 Installation Instructions

Please read and understand entire instructions before starting installation.

THANK YOU FOR CHOOSING KÜRYAKYN!

IN ORDER TO PROTECT YOU AND OTHERS FROM POSSIBLE INJURY AND/OR PROPERTY DAMAGE OR LOSS, PLEASE PAY CLOSE ATTENTION TO ALL INSTRUCTIONS, WARNINGS, CAUTIONS AND ATTENTION NOTES REGARDING THE USE AND CARE OF THIS PRODUCT.

WARNING! THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN CAN RESULT IN POTENTIAL DEATH OR SERIOUS INJURY.

ATTENTION! This indication alerts you to the fact that ignoring the contents described herein may negatively affect product performance and functionality.

TOOLS SUGGESTED

Set of Metric Combination Wrenches, Set of Metric Hex Wrenches

STRICTLY OBSERVE THE FOLLOWING GUIDELINES IN ORDER TO USE THE PRODUCT PROPERLY AND AVOID POTENTIALLY DANGEROUS ACCIDENTS.

STEP 1 Read and understand all steps in the instructions before starting the installation. Park the motorcycle on a hard, level surface and turn off the ignition.

WARNING! YOU WILL BE WORKING AROUND THE ENGINE AND EXHAUST SYSTEM DURING INSTALLATION. ENSURE THAT THE ENGINE AND EXHAUST SYSTEM HAVE FULLY COOLED TO PREVENT INJURY.

CUSTOMER SERVICE

877.370.3604 (toll free)

INSTALLATION QUESTIONS

techsupport@kuryakyn.com
or call 715.247.2983

LIMITED WARRANTY

Küryakyn warrants that any Küryakyn products sold hereunder, shall be free of defects in materials and workmanship for a period of one (1) year from the date of purchase by the consumer excepting the following provisions:

- Küryakyn shall have no obligation in the event the customer is unable to provide a receipt showing the date the customer purchased the product(s).
- The product must be properly installed, maintained and operated under normal conditions.
- Küryakyn makes no warranty, expressed or implied, with respect to any gold plated products.
- Küryakyn shall not be liable for any consequential and incidental damages, including labor and paint, resulting from failure of a Küryakyn product, failure to deliver, delay in delivery, delivery in nonconforming condition, or for any breach of contract or duty between Küryakyn and a customer.
- Küryakyn products are often intended for use in specific applications. Küryakyn makes no warranty if a Küryakyn product is used in applications other than intended.
- Küryakyn electrical products are warranted for one (1) year from the date of purchase by the consumer. L.E.D.'S contained in components of Küryakyn products will be warranted for defects in materials and workmanship for 3 years from the date of purchase where as all other components shall be warranted for one(1) year. This includes, but is not limited to; control modules, wiring, chrome & other components.

• Küryakyn makes no warranty of any kind in regard to other manufacturer's products distributed by Küryakyn. Küryakyn will pass on all warranties made by the manufacturer and where possible, will expedite the claim on behalf of the customer, but ultimately, responsibility for disposition of the warranty claim lies with the manufacturer.

ABOUT OUR CATALOG

For purchasing Küryakyn® products, you can receive a complete catalog free of charge. Send the Proof-of-Purchase below with your address to: Küryakyn, P.O. Box 339, Somerset, WI 54025. Please indicate either Accessories Catalog for Harley-Davidson® or GL & Metric Cruisers.

Be sure to ask your local dealer about other Küryakyn® products, the motorcycle parts and accessories designed for riders by riders.

©2005 Küryakyn USA® All Rights reserved.




-cont.-

7710-21MC-0911


kuryakyn.com

RIGHT SIDE

STEP 2 See PIC. 1. Remove the stock master cylinder cover. Remove or loosen the stock fasteners indicated by the arrows. Remove the engine oil dipstick and plug the hole temporarily.



STEP 3 See PIC. 2. Install the right angle bracket and the slotted bracket as shown. The slotted bracket is in a vertical orientation. The right angle bracket is placed horizontally. They can only be installed one way.




STEP 4 See PIC. 3 & 4. Shown at the left is the "waisted" bolt. Insert this bolt in the right side cover as shown. This bolt will be on the same plane as the slots in the cover. Screw the threaded spacer all the way on to this bolt until it will no longer engage the threads.






STEP 5 See PIC.5. Install the right side cover as shown. Note the location of the socket head and waisted bolts. Place plastic flat washers under the chrome bolt heads. Replace the dipstick.

LEFT SIDE

STEP 6 See PIC. 6 & 7. Remove the stock fasteners at the locations shown. Install the standoff stud and stainless flat washer as indicated. A combination wrench can be used to tighten this standoff.



ATTENTION! It is the installer's responsibility to ensure that all of the fasteners (including pre-assembled) are tightened before operation of the motorcycle. Küryakyn will not issue a warranty on components lost due to improper installation. Periodic maintenance may be required.



Ride On!