



INSTALLATION

MASTER CYLINDER RESERVOIR COVER 7820

PARTS INCLUDED

- 1 Rear Brake Master Cylinder Cover — Chrome
- 1 Threaded Hex Stand Off Spacer
- 1 M6 x 1.0 x 8mm Socket Head Cap Screw — Polished
- 4 Wave Washer
- 1 Reservoir Main Cover — Chrome
- 1 Reservoir Cap — Chrome
- 1 M6 x 1.0 x 19mm Socket Head Cap Screw — Polished
- 1 Installation Instructions

Please read and understand entire instructions before starting installation.

THANK YOU FOR CHOOSING KÜRYAKYN!

IN ORDER TO PROTECT YOU AND OTHERS FROM POSSIBLE INJURY AND/OR PROPERTY DAMAGE OR LOSS, PLEASE PAY CLOSE ATTENTION TO ALL INSTRUCTIONS, WARNINGS, CAUTIONS AND ATTENTION NOTES REGARDING THE USE AND CARE OF THIS PRODUCT.

ATTENTION! This indication alerts you to the fact that ignoring the contents described herein may negatively affect product performance and functionality.

CAUTION! This indication alerts you to the fact that ignoring the contents described herein can result in potential injury or material damage.

TOOLS SUGGESTED

Set of Metric Hex Wrenches, Set of Metric Combination Wrenches

STRICTLY OBSERVE THE FOLLOWING GUIDELINES IN ORDER TO USE THE PRODUCT PROPERLY AND AVOID POTENTIALLY DANGEROUS ACCIDENTS.

STEP 1 Read and understand all steps in the instructions before starting the installation. Park the motorcycle on a hard, level surface and turn off the ignition.

STEP 2 Remove the socket head bolt that secures the master cylinder reservoir and its stock black cover to the frame. Replace the stock cover with the new chrome one, and reinstall in the same manner as stock using the new polished M6 x 1.0 x 19mm socket head and one wave washer.

CAUTION! Do not spill brake fluid on any painted surface as damage may occur.

CUSTOMER SERVICE

877.370.3604 (toll free)

INSTALLATION QUESTIONS

techsupport@kuryakyn.com
or call 715.247.2983

LIMITED WARRANTY

Kuryakyn warrants that any Kuryakyn products sold hereunder, shall be free of defects in materials and workmanship for a period of one (1) year from the date of purchase by the consumer excepting the following provisions:

- Kuryakyn shall have no obligation in the event the customer is unable to provide a receipt showing the date the customer purchased the product(s).
 - The product must be properly installed, maintained and operated under normal conditions.
 - Kuryakyn makes no warranty, expressed or implied, with respect to any gold plated products.
 - Kuryakyn shall not be liable for any consequential and incidental damages, including labor and paint, resulting from failure of a Kuryakyn product, failure to deliver, delay in delivery, delivery in nonconforming condition, or for any breach of contract or duty between Kuryakyn and a customer.
- Kuryakyn products are often intended for use in specific applications. Kuryakyn makes no warranty if a Kuryakyn product is used in applications other than intended.
- Kuryakyn electrical products are warranted for one (1) year from the date of purchase by the consumer. L.E.D.'S contained in components of Kuryakyn products will be warranted for defects in materials and workmanship for 3 years from the date of purchase where as all other components shall be warranted for one(1) year. This includes, but is not limited to; control modules, wiring, chrome & other components.
- Kuryakyn makes no warranty of any kind in regard to other manufacturer's products distributed by Kuryakyn. Kuryakyn will pass on all warranties made by the manufacturer and where possible, will expedite the claim on behalf of the customer, but ultimately, responsibility for disposition of the warranty claim lies with the manufacturer.

ABOUT OUR CATALOG

For purchasing Kuryakyn® products, you can receive a complete catalog free of charge. Send the Proof-of-Purchase below with your address to: Kuryakyn, P.O. Box 339, Somerset, WI 54025. Please indicate either Accessories Catalog for Harley-Davidson® or GL & Metric Cruisers.

Be sure to ask your local dealer about other Kuryakyn® products, the motorcycle parts and accessories designed for riders by riders.

©2005 Kuryakyn USA® All Rights reserved.

-cont.-

7821-21MC-0911

kuryakyn.com



STEP 3 Remove the stock reservoir top cap. Carefully remove the rubber gasket and nylon seal ring from the stock cap, and install them into the new chrome cap. (See PIC.1 and PIC.2.) Replace this assembly on to the reservoir. **If any brake fluid has been spilled on any surrounding parts, wipe it up immediately.**

PIC 1



STEP 4 Remove the two acorn nuts from the master cylinder top cover. This cover will not be reinstalled. Place the 1/4" wave washer and the threaded hex standoff spacer on the front stud as shown in PIC.3.

PIC 2



STEP 5 Fasten the new master cylinder top cover in place with one of the stock acorn nuts and a wave washer (rear stud), and the polished M6 x1.0 x 8mm socket head cap screw and wave washer (front stud).

ATTENTION! It is the installer's responsibility to ensure that all of the fasteners (including pre-assembled) are tightened before operation of the motorcycle. Küryakyn will not issue a warranty on components lost due to improper installation. Periodic maintenance may be required.

PIC 4



PIC 3

