



# INSTALLATION

## CHROME NECK COVER

## 7856

### PARTS INCLUDED

- 1 Right Side Neck Cover — Chrome
- 1 #10-24 X 5/8" Socket Head Cap Screw — Chrome
- 2 M6 X 1.0 X 20mm Button Socket Cap Screw — Chrome
- 2 M6 Flat Washer — Chrome
- 1 Installation Instructions

Please read and understand entire instructions before starting installation.

### THANK YOU FOR CHOOSING KÜRYAKYN!

**IN ORDER TO PROTECT YOU AND OTHERS FROM POSSIBLE INJURY AND/OR PROPERTY DAMAGE OR LOSS, PLEASE PAY CLOSE ATTENTION TO ALL INSTRUCTIONS, WARNINGS, CAUTIONS AND ATTENTION NOTES REGARDING THE USE AND CARE OF THIS PRODUCT.**

**WARNING!** THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN CAN RESULT IN POTENTIAL DEATH OR SERIOUS INJURY.

**ATTENTION!** This indication alerts you to the fact that ignoring the contents described herein may negatively affect product performance and functionality.

**CAUTION!** This indication alerts you to the fact that ignoring the contents described herein can result in potential injury or material damage.

### TOOLS SUGGESTED

Set of Metric and Standard Hex Wrenches, Set of Metric Combination Wrenches.

**STRICTLY OBSERVE THE FOLLOWING GUIDELINES IN ORDER TO USE THE PRODUCT PROPERLY AND AVOID POTENTIALLY DANGEROUS ACCIDENTS.**

**STEP 1** Read and understand all steps in the instructions before starting the installation. Park the motorcycle on a hard, level surface and turn off the ignition. Let cool.

**WARNING!** YOU WILL BE WORKING AROUND THE ENGINE AND EXHAUST SYSTEM DURING INSTALLATION. ENSURE THAT THE ENGINE AND EXHAUST SYSTEM HAVE FULLY COOLED TO PREVENT INJURY.

**ATTENTION!** A factory service manual may be helpful in performing this installation. Do not attempt to perform this installation if you are not confident in your ability to complete all of the steps in the procedure; consult a trained technician.

**STEP 2** Remove seat.

-cont.-

7856-21MC-0911



### CUSTOMER SERVICE

877.370.3604 (toll free)

### INSTALLATION QUESTIONS

techsupport@kuryakyn.com  
or call 715.247.2983

### LIMITED WARRANTY

Küryakyn warrants that any Küryakyn products sold hereunder, shall be free of defects in materials and workmanship for a period of one (1) year from the date of purchase by the consumer excepting the following provisions:

- Küryakyn shall have no obligation in the event the customer is unable to provide a receipt showing the date the customer purchased the product(s).
  - The product must be properly installed, maintained and operated under normal conditions.
  - Küryakyn makes no warranty, expressed or implied, with respect to any gold plated products.
  - Küryakyn shall not be liable for any consequential and incidental damages, including labor and paint, resulting from failure of a Küryakyn product, failure to deliver, delay in delivery, delivery in nonconforming condition, or for any breach of contract or duty between Küryakyn and a customer.
- Küryakyn products are often intended for use in specific applications. Küryakyn makes no warranty if a Küryakyn product is used in applications other than intended.
- Küryakyn electrical products are warranted for one (1) year from the date of purchase by the consumer. L.E.D.'S contained in components of Küryakyn products will be warranted for defects in materials and workmanship for 3 years from the date of purchase where as all other components shall be warranted for one(1) year. This includes, but is not limited to; control modules, wiring, chrome & other components.

• Küryakyn makes no warranty of any kind in regard to other manufacturer's products distributed by Küryakyn. Küryakyn will pass on all warranties made by the manufacturer and where possible, will expedite the claim on behalf of the customer, but ultimately, responsibility for disposition of the warranty claim lies with the manufacturer.

### ABOUT OUR CATALOG

For purchasing Küryakyn® products, you can receive a complete catalog free of charge. Send the Proof-of-Purchase below with your address to: Küryakyn, P.O. Box 339, Somerset, WI 54025. Please indicate either Accessories Catalog for Harley-Davidson® or GL & Metric Cruisers.

Be sure to ask your local dealer about other Küryakyn® products, the motorcycle parts and accessories designed for riders by riders.

©2005 Küryakyn USA® All Rights reserved.



kuryakyn.com

**ATTENTION!** Assistance recommended in securing the fuel tank after all of the fasteners have been removed to prevent damage.

**STEP 3** Unbolt the rear of fuel tank and slide the tank back 4–6 inches. Be very careful not to stretch or break loose the attached vent or fuel lines. You may want to employ the help of a friend to make sure the tank does not fall off the bike.

**CAUTION!** Avoid damage to the motorcycle. Protect painted surfaces with a soft cloth or blanket.

**STEP 4** Gently remove the two rubber tank stops that hold the front of the tank in place by pulling directly outward.

**STEP 5** Remove the two stock M6 fasteners located on the bottom of the stock neck cover.

**STEP 6** Notice the clutch cable is routed in front of the left cover. Remove the stock neck cover by lifting the bottom of the covers upward and outward gently until the male/female interlock at the top center of the covers release from each other. Remove the right side cover, and then the left.

**STEP 7** Set the chrome neck covers loosely in place. Route the clutch cable in front of the left cover.

**STEP 8** Insert the supplied #10–24 X 5/8" socket head cap screw through the fastener hole at the top of the left cover and loosely fasten to the right cover.

**STEP 9** Insert the supplied M6 X 1.0 X 20mm button socket cap screws with M6 flat washers through the lower fastener holes on the bottom side of each neck cover into the OEM neck cover mounting holes and loosely fasten to the frame.

**STEP 10** Tighten the fastener at the top of the cover, and then the two lower fasteners.

**ATTENTION!** It is the installer's responsibility to ensure that all of the fasteners (including pre-assembled) are tightened before operation of the motorcycle. Küryakyn will not issue a warranty on components lost due to improper installation. Periodic maintenance may be required.

**STEP 11** Replace the two rubber tank stops removed in STEP 4.

**STEP 12** Reinstall the tank in the same fashion as it was removed in STEP 3. Be extremely careful not to pinch any fuel or vent lines.

**ATTENTION!** Secure all hoses away from any moving parts, pinch points or extreme heat. Küryakyn WILL NOT issue a warranty on any component that fails due to pinched, crimped, broken, abraded or melted hoses.

**STEP 13** Reinstall the seat.