MOTOREX Oil of Switzerland
Revision: 17.04.2023

Printing date 17.04.2023

Version number 2.0 (replaces version 1.0)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: AIR FILTER OIL SPRAY
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture

Air filter oil

Only for proper handling.

- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

MOTOREX AG

Bern-Zürich-Strasse 31, Postfach

CH-4901 Langenthal

Tel. +41 (0)62 919 75 75

www.motorex.com

- · Further information obtainable from: msds@motorex.com
- · 1.4 Emergency telephone number:

In case of a medical emergency following exposure to a chemical, the public should call NHS Direct in England or Wales 0845 46 47 or NHS 24 in Scotland 08454 24 24 (UK only).

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if

heated.

STOT SE 3 H336 May cause drowsiness or dizziness.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways. Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms





GHS02 GHS07

- · Signal word Danger
- · Hazard-determining components of labelling:

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

Distillates (petroleum), hydrotreated light paraffinic

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

(Contd. on page 2)

MOTOREX Oil of Switzerland
Revision: 17.04.2023

Printing date 17.04.2023

Version number 2.0 (replaces version 1.0)

Trade name: AIR FILTER OIL SPRAY

(Contd. of page 1)

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- PBT: Not applicable.vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:			
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-32	butane, pure Flam. Gas 1A, H220; Press. Gas (Comp.), H280	25-50%	
EC number: 920-750-0 Reg.nr.: 01-2119473851-33	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H336	≥20-<25%	
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21	propane Flam. Gas 1A, H220; Press. Gas (Comp.), H280	10-25%	
CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0 Reg.nr.: 01-2119485395-27	isobutane Flam. Gas 1A, H220; Press. Gas (Comp.), H280	1-2.5%	

· Regulation (EC) No 648/2004 on detergents / Labelling for contents aliphatic hydrocarbons ≥15 - <30%

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed
- No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

GB

[•] Additional information: For the wording of the listed hazard phrases refer to section 16.

MOTOREX*
Oil of Switzerland

Revision: 17.04.2023

Printing date 17.04.2023

Version number 2.0 (replaces version 1.0)

Trade name: AIR FILTER OIL SPRAY

(Contd. of page 2)

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- Information about fire and explosion protection:

Keep ignition sources away - Do not smoke.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

Do not spray onto a naked flame or any incandescent material.

- · 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- · Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

The recommended storage temperature is (deg.C): ≤ 50°C

Keep container tightly sealed.

- Storage class: 2 B
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

106-97-8 butane, pure

WEL Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm

Carc (if more than 0.1% of buta-1.3-diene)

(Contd. on page 4)

MOTOREX*
Oil of Switzerland

Revision: 17.04.2023

Printing date 17.04.2023

Version number 2.0 (replaces version 1.0)

Trade name: AIR FILTER OIL SPRAY

(Contd. of page 3)

· DNELs		, , ,
Hydrocar	bons, C7-C9, n-alkanes, isoalkanes, cyclics	
Oral	DNEL/general population/Systemic effects/Long-term	699 mg/kg/24h (consumer)
Dermal	DNEL / Workers / Systemic effects / Long-term	773 mg/kg/24h (worker)
	DNEL/general population/Systemic effects/Long-term	699 mg/kg/24h (consumer)
Inhalative	DNEL / Workers / Systemic effects / Long-term	2,035 mg/m3 (worker)
	DNEL/general population/Systemic effects/Long-term	608 mg/m3 (consumer)

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Not necessary if room is well-ventilated.

Respiratory protection if formation of aerosol or mist: use mask with filter type A2, A2/P2 or ABEK.

· Hand protection

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- · Eye/face protection Not required.
- · Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

Physical state
Colour:
Odour:
Odour threshold:
Melting point/freezing point:

Aerosol
Blue
Solvent-like
Not determined.
Undetermined.

Boiling point or initial boiling point and

boiling range Not applicable, as aerosol.

· Flammability Not applicable.

· Lower and upper explosion limit

· Lower: 0.9 Vol %
 · Upper: 6.8 Vol %
 · Flash point: <-50 °C

Auto-ignition temperature: 310 °C (DIN 51794)
 Decomposition temperature: Not determined.

(Contd. on page 5)

Revision: 17.04.2023

Printing date 17.04.2023

Version number 2.0 (replaces version 1.0)

Trade name: AIR FILTER OIL SPRAY

(Contd. of page 4)

Not determined. · pH

· Viscositv:

· Kinematic viscosity 15.5 mm²/s @ 40 °C

· Consistency

· Dynamic: Not determined.

Solubility

· water: Not miscible or difficult to mix.

· Partition coefficient n-octanol/water (log

value) Not determined.

Heat Capacity

Vapour pressure at 20 °C: 30 hPa

Vapour pressure:

Density and/or relative density

Density at 20 °C: 0.81 g/cm³ (ASTM D 4052)

Relative density Not determined. Vapour density Not determined.

· 9.2 Other information

· Appearance:

· Form: Liquefied gas

· Important information on protection of health

and environment, and on safety.

Product is not explosive. However, formation of · Explosive properties:

explosive air/vapour mixtures are possible.

· Solvent separation test:

· VOC (EC) 79.17 %

· Change in condition

· Evaporation rate Not applicable.

· Information with regard to physical hazard

classes

· Explosives Void · Flammable gases Void

· Aerosols Extremely flammable aerosol. Pressurised

container: May burst if heated.

· Oxidising gases Void · Gases under pressure Void · Flammable liquids Void Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Void · Self-heating substances and mixtures Void

· Substances and mixtures, which emit flammable gases in contact with water Void · Oxidising liquids Void Oxidising solids Void · Organic peroxides Void · Corrosive to metals Void · Desensitised explosives Void

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

(Contd. on page 6)

MOTOREX
Oil of Switzerland
Revision: 17.04.2023

Printing date 17.04.2023

Version number 2.0 (replaces version 1.0)

Trade name: AIR FILTER OIL SPRAY

(Contd. of page 5)

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:				
106-97-8 butane, pure				
Inhalative LC50 / 15 min 1,442.738-1.443 mg/l (rat)				
		800,000 ppm (rat)		
	LC50 / 2h	1,237 mg/l (mouse)		
	LC50 / 2h	520,400-539,600 ppm (mouse)		
	LC50 / 4h	658 mg/l (rat)		
	NOAEC	4,000-16,000 ppm (rat)		
	NOAEC	7.2-21.4 mg/l (rat)		
	LOAEC	21.6 mg/l (rat)		
	LOAEC	12,000 ppm (rat)		
Hydrocar	bons, C7-C9, n	-alkanes, isoalkanes, cyclics		
Oral	LD50	8 ml/kg (rat)		
Dermal	LD50	4 ml/kg (rat)		
	LD50	2,800-3,100 mg/kg (rat)		
Inhalative	LC50 / 4h	23.3 mg/l (rat)		
	NOAEC	5.8-24.3 mg/l (rat)		
74-98-6 pi	-			
Inhalative	LC50 / 15 min	1,442.738-1.443 mg/l (rat)		
	LC50 / 15 min	800,000 ppm (rat)		
	LC50 / 2h	1,237 mg/l (mouse)		
	LC50 / 2h	520,400-539,600 ppm (mouse)		
	NOAEC	4,000-16,000 ppm (rat)		
	NOAEC	7.214-21.394 mg/l (rat)		
	LOAEC	21.64 mg/l (rat)		
	LOAEC	12,000 ppm (rat)		
75-28-5 is				
Inhalative		1,442.738-1.443 mg/l (rat)		
		800,000 ppm (rat)		
	LC50 / 2h	1,237 mg/l (mouse)		
	LC50 / 2h	520,400-539,600 ppm (mouse)		
	NOAEC	4,000-16,000 ppm (rat)		
	NOAEC	7.214-21.394 mg/l (rat)		
	LOAEC	21.641 mg/l (rat)		
	LOAEC	12,000 ppm (rat)		

- · STOT-single exposure May cause drowsiness or dizziness.
- · Aspiration hazard May be fatal if swallowed and enters airways.

(Contd. on page 7)

Revision: 17.04.2023

Printing date 17.04.2023

Version number 2.0 (replaces version 1.0)

Trade name: AIR FILTER OIL SPRAY

(Contd. of page 6)

 11.2 Information on oth 	ner hazards
---------------------------------------------	-------------

· Endocrine disrupting properties

None of the ingredients is listed.

	N 12: Ecol	agical in	tormation
SECIIC	M 12. EGUI	vulcal III	

	•	_	-	
12.	7	To	XIC	IIV

12.1 To	•
•	toxicity: 8 butane, pure
LC50	24.1-147.5 mg/l/96h (fish)
LC50 LC50	14.2-69.4 mg/l/48h (aquatic invertebrates)
EC50	7.7-19.4 mg/l/96h (algae / cyanobacteria)
	arbons, C7-C9, n-alkanes, isoalkanes, cyclics
EC50	0.23 mg/l/21d (aquatic invertebrates)
EC50	0.64 mg/l/48h (aquatic invertebrates)
LL50	3-10 mg/l/96h (fish)
LL50	10-30 mg/l/72h (fish)
LL50	10-30 mg/l/48h (fish)
LL50	30-100 mg/l/24h (fish)
LL0	3 mg/l/96h (fish)
EL50	13 mg/l/96h (algae / cyanobacteria)
EL50	4.6-10 mg/l/48h (aquatic invertebrates)
	10-30 mg/l/48h (algae / cyanobacteria)
EL50	10-22 mg/l/24h (aquatic invertebrates)
	10-30 mg/l/24h (algae / cyanobacteria)
EL50	10-30 mg/l/72h (algae / cyanobacteria)
EL0	4.6 mg/l/48h (aquatic invertebrates)
EL0	10 mg/l/24h (aquatic invertebrates)
NOEC	0.17 mg/l/21d (aquatic invertebrates)
NOELR	0.574 mg/l/28d (fish)
NOELR	1 mg/l/21d (aquatic invertebrates)
NOELR	6.3 mg/l/96h (algae / cyanobacteria)
LOEC	0.32 mg/kg/28d (aquatic invertebrates)
74-98-6	propane
LC50	24.11-147.54 mg/l/96h (fish)
LC50	14.22-69.43 mg/l/48h (aquatic invertebrates)
EC50	7.71-19.37 mg/l/96h (algae / cyanobacteria)
	isobutane
LC50	24.11-147.54 mg/l/96h (fish)
LC50	14.22-69.43 mg/l/48h (aquatic invertebrates)
EC50	7.71-19.37 mg/l/96h (algae / cyanobacteria)

• 12.2 Persistence and degradability No further relevant information available.

106-97-8 butane, pure

Partition coefficient | 1.09-2.8 [---] (log Kow) (Bioaccumulation)

(Contd. on page 8)

MOTOREX Oil of Switzerland
Revision: 17.04.2023

Printing date 17.04.2023

Version number 2.0 (replaces version 1.0)

Trade name: AIR FILTER OIL SPRAY

		(Contd. of page 7)
Hydrocarbons, C7	-C9, n-alkanes, isoalkanes, cyclics	
Biodegradability	98 % (28d) (Biodegradability) (OECD 301 F)	
74-98-6 propane		
Partition coefficient	1.09-2.8 [] (log Kow) (Bioaccumulation)	
75-28-5 isobutane		
Partition coefficient	1.09-2.8 [] (log Kow) (Bioaccumulation)	
Biodegradability	100 % (28d) (Biodegradability)	

- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Harmful to aquatic organisms

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Contact waste processors for recycling information.

Return product and/or partially emptied container in original packaging to the point of sale or hand it over to a collection point for special waste.

- Uncleaned packaging:
- Recommendation:

Disposal must be made according to official regulations.

Discharged containers can contain flammable or explosive vapours.

SECTION 14: Transport information

· 14.1 UN number or ID number

· ADR/RID/ADN, IMDG, IATA UN1950

· 14.2 UN proper shipping name

· ADR/RID/ADN 1950 AEROSOLS · IMDG AEROSOLS

· IATA AEROSOLS, flammable

- · 14.3 Transport hazard class(es)
- · ADR/RID/ADN



· Class 2 5F Gases.

(Contd. on page 9)

MOTOREX Oil of Switzerland
Revision: 17.04.2023

Printing date 17.04.2023

Version number 2.0 (replaces version 1.0)

Trade name: AIR FILTER OIL SPRAY

	(Contd. of page 8
· Label	2.1
· IMDG, IATA	
· Class · Label	2.1 Gases. 2.1
· 14.4 Packing group · ADR/RID/ADN, IMDG, IATA	Void
· 14.5 Environmental hazards:	Not applicable.
· 14.6 Special precautions for user · Hazard identification number (Kemler of · EMS Number: · Stowage Code · Segregation Code	F-D,S-U SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacit of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTI AEROSOLS: Category C, Clear of living quarters. SG69 For AEROSOLS with a maximum capacit of 1 litre: Segregation as for class 9. Stow "separated from class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· 14.7 Maritime transport in bulk accords IMO instruments	ing to Not applicable.
Transport/Additional information:	
· ADR/RID/ADN · Limited quantities (LQ) · Excepted quantities (EQ) · Transport category · Tunnel restriction code	1L Code: E0 Not permitted as Excepted Quantity 2 D
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E0 Not permitted as Excepted Quantity
UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.

(Contd. on page 10)

MOTOREX Oil of Switzerland
Revision: 17.04.2023

Printing date 17.04.2023

Version number 2.0 (replaces version 1.0)

Trade name: AIR FILTER OIL SPRAY

(Contd. of page 9)

- · Seveso category P3a FLAMMABLE AEROSOLS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. The classification of the mixture was carried out by calculation in accordance with the rules laid down in Annex I of Regulation (EC) No 1272/2008.

No special training instructions to ensure protection of human health and environment are required.

- · purity requirement
- · Relevant phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

- · Department issuing SDS: Abteilung Produktsicherheit
- Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1A: Flammable gases - Category 1A

Aerosol 1: Aerosols - Category 1

Press. Gas (Comp.): Gases under pressure - Compressed gas

Flam. Liq. 2: Flammable liquids - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· * Data compared to the previous version altered.

Annex: Exposure scenario 1

- · Short title of the exposure scenario Industrial use of lubricants and greases in open systems
- Sector of Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

- · Product category PC24 Lubricants, greases, release products
- · Process category

PROC1 Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.

PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions

PROC7 Industrial spraying

(Contd. on page 11)

MOTOREX Oil of Switzerland
Revision: 17.04.2023

Printing date 17.04.2023

Version number 2.0 (replaces version 1.0)

Trade name: AIR FILTER OIL SPRAY

(Contd. of page 10)

PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities

PROC9 Transfer of substance or mixture into small containers (dedicated filling line, including weighing)

PROC10 Roller application or brushing

PROC13 Treatment of articles by dipping and pouring

Environmental release category

ERC4 Use of non-reactive processing aid at industrial site (no inclusion into or onto article)

· Description of the activities / processes covered in the Exposure Scenario

See section 1 of the annex to the Safety Data Sheet.

- · Conditions of use
- · Duration and frequency 5 workdays/week.
- · Physical parameters
- Physical state Fluid
- · Concentration of the substance in the mixture The substance is main component.
- Other operational conditions
- · Other operational conditions affecting environmental exposure No special measures required.
- · Other operational conditions affecting consumer exposure Not required.
- · Other operational conditions affecting consumer exposure during the use of the product Not applicable.
- Risk management measures
- · Worker protection
- · Organisational protective measures No special measures required.
- Technical protective measures No special measures required.
- Personal protective measures No special measures required.
- Measures for consumer protection No special measures required.
- Environmental protection measures
- Air No special measures required.
- · Water No special measures required.
- Disposal measures

Disposal must be made according to official regulations.

Ensure that waste is collected and contained.

- · Disposal procedures Dispose of product residues with household waste.
- Waste type Partially emptied and uncleaned packaging
- · Exposure estimation
- · Consumer Not relevant for this Exposure Scenario.
- · Guidance for downstream users No further relevant information available.

Annex: Exposure scenario 2

- · Short title of the exposure scenario Professional use of lubricants and greases in open systems
- Sector of Use

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- · Product category PC24 Lubricants, greases, release products
- Process category

PROC1 Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.

PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions

PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

PROC10 Roller application or brushing

PROC11 Non industrial spraying

PROC13 Treatment of articles by dipping and pouring

Environmental release category

ERC8a Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor)

ERC8d Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)

(Contd. on page 12)

Article 31

version 1.0)

Revision: 17.04,2023

Printing date 17.04.2023

Version number 2.0 (replaces version 1.0)

Trade name: AIR FILTER OIL SPRAY

(Contd. of page 11)

- Description of the activities / processes covered in the Exposure Scenario See section 1 of the annex to the Safety Data Sheet.
- · Conditions of use
- · Duration and frequency 5 workdays/week.
- · Physical parameters
- · Physical state Fluid
- · Concentration of the substance in the mixture The substance is main component.
- · Other operational conditions
- Other operational conditions affecting environmental exposure No special measures required.
- · Other operational conditions affecting consumer exposure Not required.
- Other operational conditions affecting consumer exposure during the use of the product Not applicable.
- Risk management measures
- · Worker protection
- · Organisational protective measures No special measures required.
- · Technical protective measures No special measures required.
- · Personal protective measures No special measures required.
- · Measures for consumer protection No special measures required.
- · Environmental protection measures
- · Air No special measures required.
- · Water No special measures required.
- · Disposal measures

Disposal must be made according to official regulations.

Ensure that waste is collected and contained.

- · Disposal procedures Dispose of product residues with household waste.
- · Waste type Partially emptied and uncleaned packaging
- · Exposure estimation
- · Consumer Not relevant for this Exposure Scenario.
- · Guidance for downstream users No further relevant information available.

Annex: Exposure scenario 3

- · Short title of the exposure scenario Private use of lubricants and greases in open systems
- · Sector of Use SU21 Consumer uses: Private households / general public / consumers
- · Product category PC24 Lubricants, greases, release products
- Environmental release category

ERC8a Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor)
ERC8d Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)

- Description of the activities / processes covered in the Exposure Scenario See section 1 of the annex to the Safety Data Sheet.
- · Conditions of use
- · Duration and frequency 5 workdays/week.
- Physical parameters
- Physical state Fluid
- Concentration of the substance in the mixture The substance is main component.
- · Other operational conditions
- Other operational conditions affecting environmental exposure No special measures required.
- Other operational conditions affecting consumer exposure Not required.
- Other operational conditions affecting consumer exposure during the use of the product Not applicable.
- Risk management measures
- · Worker protection
- Organisational protective measures No special measures required.
- · Technical protective measures No special measures required.
- · Personal protective measures No special measures required.
- Measures for consumer protection No special measures required.

(Contd. on page 13)

MOTOREX Oil of Switzerland
Revision: 17.04.2023

Printing date 17.04.2023

Version number 2.0 (replaces version 1.0)

Trade name: AIR FILTER OIL SPRAY

(Contd. of page 12)

- · Environmental protection measures
- · Air No special measures required.
- · Water No special measures required.
- · Disposal measures

Disposal must be made according to official regulations.

Ensure that waste is collected and contained.

- · Disposal procedures Dispose of product residues with household waste.
- Waste type Partially emptied and uncleaned packaging
- · Exposure estimation
- · Consumer Not relevant for this Exposure Scenario.
- · Guidance for downstream users No further relevant information available.

Annex: Exposure scenario 4

- · Short title of the exposure scenario Industrial use of sprays
- · Sector of Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

· Product category

PC14 Metal surface treatment products

PC34 Textile dyes, and impregnating products

- Process category PROC11 Non industrial spraying
- Environmental release category

ERC8a Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) ERC8d Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)

Description of the activities / processes covered in the Exposure Scenario See section 1 of the annex to the Safety Data Sheet.

- · Conditions of use
- · Duration and frequency 5 workdays/week.
- · Physical parameters
- · Physical state Fluid
- · Concentration of the substance in the mixture The substance is main component.
- Other operational conditions
- Other operational conditions affecting environmental exposure No special measures required.
- · Other operational conditions affecting consumer exposure Not required.
- Other operational conditions affecting consumer exposure during the use of the product Not applicable.
- · Risk management measures
- · Worker protection
- · Organisational protective measures No special measures required.
- · Technical protective measures No special measures required.
- Personal protective measures No special measures required.
- Measures for consumer protection No special measures required.
- · Environmental protection measures
- · Air No special measures required.
- · Water No special measures required.
- · Disposal measures Ensure that waste is collected and contained.
- · Disposal procedures Dispose of product residues with household waste.
- · Waste type Partially emptied and uncleaned packaging
- Exposure estimation
- · Consumer Not relevant for this Exposure Scenario.
- Guidance for downstream users No further relevant information available.

Annex: Exposure scenario 5

· Short title of the exposure scenario Professional use of sprays

(Contd. on page 14)

MOTOREX*
Oil of Switzerland
Revision: 17.04.2023

Printing date 17.04.2023

Version number 2.0 (replaces version 1.0)

Trade name: AIR FILTER OIL SPRAY

(Contd. of page 13)

· Sector of Use

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

· Product category

PC14 Metal surface treatment products

PC34 Textile dyes, and impregnating products

- · Process category PROC11 Non industrial spraying
- Environmental release category

ERC8a Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor)
ERC8d Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)

• Description of the activities / processes covered in the Exposure Scenario See section 1 of the annex to the Safety Data Sheet.

- · Conditions of use
- · Duration and frequency 5 workdays/week.
- · Physical parameters
- · Physical state Fluid
- · Concentration of the substance in the mixture The substance is main component.
- · Other operational conditions
- Other operational conditions affecting environmental exposure No special measures required.
- Other operational conditions affecting consumer exposure Not required.
- Other operational conditions affecting consumer exposure during the use of the product Not applicable.
- Risk management measures
- · Worker protection
- Organisational protective measures No special measures required.
- Technical protective measures No special measures required.
- Personal protective measures No special measures required.
- · Measures for consumer protection No special measures required.
- · Environmental protection measures
- Air No special measures required.
- · Water No special measures required.
- · Disposal measures Ensure that waste is collected and contained.
- Disposal procedures Dispose of product residues with household waste.
- · Waste type Partially emptied and uncleaned packaging
- · Exposure estimation
- · Consumer Not relevant for this Exposure Scenario.
- · Guidance for downstream users No further relevant information available.

Annex: Exposure scenario 6

- · Short title of the exposure scenario Private use of sprays
- Sector of Use SU21 Consumer uses: Private households / general public / consumers
- · Product category

PC14 Metal surface treatment products

PC34 Textile dyes, and impregnating products

- · Process category PROC11 Non industrial spraying
- Environmental release category

ERC8a Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) ERC8d Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)

Description of the activities / processes covered in the Exposure Scenario

See section 1 of the annex to the Safety Data Sheet.

- · Conditions of use
- · Duration and frequency 5 workdays/week.
- · Physical parameters
- · Physical state Fluid
- · Concentration of the substance in the mixture The substance is main component.

(Contd. on page 15)

MOTOREX*
Oil of Switzerland

Revision: 17.04.2023

Printing date 17.04.2023

Version number 2.0 (replaces version 1.0)

Trade name: AIR FILTER OIL SPRAY

(Contd. of page 14)

- · Other operational conditions
- Other operational conditions affecting environmental exposure No special measures required.
- Other operational conditions affecting consumer exposure Not required.
- · Other operational conditions affecting consumer exposure during the use of the product Not applicable.
- Risk management measures
- · Worker protection
- · Organisational protective measures No special measures required.
- Technical protective measures No special measures required.
- Personal protective measures No special measures required.
- · Measures for consumer protection No special measures required.
- Environmental protection measures
- Air No special measures required.
- · Water No special measures required.
- Disposal measures Ensure that waste is collected and contained.
- · Disposal procedures Dispose of product residues with household waste.
- Waste type Partially emptied and uncleaned packaging
- · Exposure estimation
- · Consumer Not relevant for this Exposure Scenario.
- Guidance for downstream users No further relevant information available.

GB