

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name: POWER SYNT 4T SAE 10W/50 JASO MA2**
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**  
No further relevant information available.
- **Application of the substance / the mixture**  
Only for proper handling.  
Engine oil
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
MOTOREX AG  
Bern-Zürich-Strasse 31, Postfach  
CH-4901 Langenthal  
Tel. +41 (0)62 919 75 75  
www.motorex.com
- **Further information obtainable from: msds@motorex.com**
- **1.4 Emergency telephone number:**  
In case of a medical emergency following exposure to a chemical, the public should call NHS Direct in England or Wales 0845 46 47 or NHS 24 in Scotland 08454 24 24 24 (UK only).

## SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**  
Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.
- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**  
The product is classified and labelled according to the GB CLP regulation.
- **Hazard pictograms** Void
- **Signal word** Void
- **Hazard statements**  
H412 Harmful to aquatic life with long lasting effects.
- **Precautionary statements**  
P101 If medical advice is needed, have product container or label at hand.  
P102 Keep out of reach of children.  
P103 Read carefully and follow all instructions.  
P273 Avoid release to the environment.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

## SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**
- **Description:** Mixture of substances listed below with nonhazardous additions.

- **Dangerous components:**

CAS: 64742-54-7 EINECS: 265-157-1 Index number: 649-467-00-8 Reg.nr.: 01-2119484627-25	Distillates (petroleum), hydrotreated heavy paraffinic Asp. Tox. 1, H304	2.5-7.5%
---	---	----------

(Contd. on page 2)

# Safety data sheet

## according to 1907/2006/EC, Article 31



Printing date 30.10.2023

Version number 3.1 (replaces version 3.0)

Revision: 30.10.2023

**Trade name: POWER SYNT 4T SAE 10W/50 JASO MA2**

(Contd. of page 1)

CAS: 64742-65-0 EINECS: 265-169-7 Index number: 649-474-00-6 Reg.nr.: 01-2119471299-27	Distillates (petroleum), solvent-dewaxed heavy paraffinic ----- Asp. Tox. 1, H304	≥0.25-≤2.5%
CAS: 85940-28-9 EINECS: 288-917-4	Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl) and iso-Bu and iso-Pr esters, zinc salts Eye Dam. 1, H318; Aquatic Chronic 2, H411; Skin Irrit. 2, H315 Specific concentration limits: Skin Irrit. 2; H315: C ≥ 15% Eye Dam. 1; H318: C ≥ 20 % Eye Irrit. 2; H319: 15 % ≤ C < 20 %	≥0.25-<2.5%
CAS: 128-39-2 EINECS: 204-884-0 Reg.nr.: 01-2119490822-33	2,6-di-tert-butylphenol ----- Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Irrit. 2, H315	≥0.25-≤1%

**Additional information:**

Note L: The classification as carcinogen does not apply because the mixture (or substance) contains less than 3% dimethyl sulfoxide extract (DMSO), measured according to IP 346.

For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

**4.1 Description of first aid measures**

- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.

**4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

**4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

### SECTION 5: Firefighting measures

**5.1 Extinguishing media**

- **Suitable extinguishing agents:** Use fire extinguishing methods suitable to surrounding conditions.

**5.2 Special hazards arising from the substance or mixture**

No further relevant information available.

**5.3 Advice for firefighters**

- **Protective equipment:** No special measures required.

### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Not required.

**6.2 Environmental precautions:**

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

**6.3 Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

**6.4 Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 3)

**Trade name: POWER SYNT 4T SAE 10W/50 JASO MA2**

See Section 13 for disposal information.

(Contd. of page 2)

## SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** No special precautions are necessary if used correctly.
- **Information about fire - and explosion protection:** No special measures required.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**  
The recommended storage temperature is (deg.C): ≤50°C
- **Storage class:** 10
- **7.3 Specific end use(s)** No further relevant information available.

## SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**
- **Ingredients with limit values that require monitoring at the workplace:**  
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

### · DNELs

#### 64742-65-0 Distillates (petroleum), solvent-dewaxed heavy paraffinic

Inhalative	DNEL	5.4 mg/m <sup>3</sup> /8h (worker)
	DNEL	1.2 mg/m <sup>3</sup> /24h (consumer)

#### 128-39-2 2,6-di-tert-butylphenol

Oral	DNEL/general population/Systemic effects/Long-term	6.75 mg/kg/24h (consumer)
Dermal	DNEL / Workers / Systemic effects / Long-term	11.25 mg/kg/24h (worker)
Inhalative	DNEL / Workers / Systemic effects / Long-term	70.61 mg/m <sup>3</sup> (worker)
	DNEL/general population/Systemic effects/Long-term	20.9 mg/m <sup>3</sup> (consumer)

### · PNECs

#### 128-39-2 2,6-di-tert-butylphenol

Oral	PNEC / Predators / Secondary poisoning	60 mg/kg food (secondary poisoning (predators))
	PNEC / Aquatic organisms / Freshwater	0.0007-0.011 mg/l (aquatic organisms)
	PNEC / Aquatic organisms / Marine water	0.00007-0.011 mg/l (aquatic organisms)
	PNEC / Aquatic org / intermittent releases (freshwater)	0.0045 mg/l (aquatic organisms)
	PNEC / Aquatic organisms / Sewage treatment plant/STP	10 mg/l (aquatic organisms)
	PNEC / Aquatic organisms / Sediment (freshwater)	0.317-1.56 mg/kg (aquatic organisms)
	PNEC / Aquatic organisms / Sediment (marine water)	0.0317-1.56 mg/kg (aquatic organisms)
	PNEC / Terrestrial organism / Soil	0.063-0.746 mg/kg (terrestrial organisms)

- **Additional information:** The lists valid during the making were used as basis.
- **8.2 Exposure controls**
- **Appropriate engineering controls** No further data; see section 7.

(Contd. on page 4)

**Trade name: POWER SYNT 4T SAE 10W/50 JASO MA2**

(Contd. of page 3)

- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures:**  
Keep away from foodstuffs, beverages and feed.  
Wash hands before breaks and at the end of work.  
Do not inhale gases / fumes / aerosols.
- **Respiratory protection:**  
Not necessary if room is well-ventilated.  
Respiratory protection if formation of aerosol or mist: use mask with filter type A2, A2/P2 or ABEK.
- **Hand protection**  
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.  
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
- **Material of gloves**  
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**  
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye/face protection** Goggles recommended during refilling
- **Body protection:** Protective work clothing

## SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**
- **General Information**
- **Physical state** Fluid
- **Colour:** Brown
- **Odour:** Characteristic
- **Odour threshold:** Not determined.
- **Melting point/freezing point:** Undetermined.
- **Boiling point or initial boiling point and boiling range** Undetermined.
- **Flammability** Not applicable.
- **Lower and upper explosion limit**
- **Lower:** Not determined.
- **Upper:** Not determined.
- **Flash point:** >200 °C
- **Decomposition temperature:** Not determined.
- **pH** Not determined.
- **Viscosity:**
- **Kinematic viscosity** 111.8 mm<sup>2</sup>/s @ 40 °C
- **Consistency**
- **Dynamic:** Not determined.
- **Solubility**
- **water:** Not miscible or difficult to mix.
- **Partition coefficient n-octanol/water (log value)** Not determined.
- **Heat Capacity**
- **Vapour pressure:** Not determined.
- **Density and/or relative density**
- **Density at 20 °C:** 0.854 g/cm<sup>3</sup> (ASTM D 4052)
- **Relative density** Not determined.

(Contd. on page 5)

# Safety data sheet

according to 1907/2006/EC, Article 31



Printing date 30.10.2023

Version number 3.1 (replaces version 3.0)

Revision: 30.10.2023

Trade name: POWER SYNT 4T SAE 10W/50 JASO MA2

(Contd. of page 4)

· Vapour density	Not determined.
· <b>9.2 Other information</b>	
· <b>Appearance:</b>	
· <b>Form:</b>	Fluid
· <b>Important information on protection of health and environment, and on safety.</b>	
· <b>Explosive properties:</b>	Product does not present an explosion hazard.
· <b>Solvent separation test:</b>	
· <b>VOC (EC)</b>	0.00 %
· <b>Change in condition</b>	
· <b>Solidification point:</b>	
· <b>Pouring point</b>	-43.6 °C
· <b>Evaporation rate</b>	Not determined.
· <b>Information with regard to physical hazard classes</b>	
· <b>Explosives</b>	Void
· <b>Flammable gases</b>	Void
· <b>Aerosols</b>	Void
· <b>Oxidising gases</b>	Void
· <b>Gases under pressure</b>	Void
· <b>Flammable liquids</b>	Void
· <b>Flammable solids</b>	Void
· <b>Self-reactive substances and mixtures</b>	Void
· <b>Pyrophoric liquids</b>	Void
· <b>Pyrophoric solids</b>	Void
· <b>Self-heating substances and mixtures</b>	Void
· <b>Substances and mixtures, which emit flammable gases in contact with water</b>	Void
· <b>Oxidising liquids</b>	Void
· <b>Oxidising solids</b>	Void
· <b>Organic peroxides</b>	Void
· <b>Corrosive to metals</b>	Void
· <b>Desensitised explosives</b>	Void

## SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

## SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

### · **LD/LC50 values relevant for classification:**

**64742-54-7 Distillates (petroleum), hydrotreated heavy paraffinic**

Oral	LD50	5,000 mg/kg (rat)
------	------	-------------------

(Contd. on page 6)

# Safety data sheet

according to 1907/2006/EC, Article 31



Printing date 30.10.2023

Version number 3.1 (replaces version 3.0)

Revision: 30.10.2023

**Trade name: POWER SYNT 4T SAE 10W/50 JASO MA2**

(Contd. of page 5)

Dermal	LOAEL	125 mg/kg/24h (rat)
	LD50	2,000-5,000 mg/kg (rabbit)
	NOAEL	150 mg/kg/24h (mouse) 30-2,000 mg/kg/24h (rat)
Inhalative		1,000 mg/kg/24h (rabbit)
	LOAEL	100 mg/kg/24h (mouse)
	LC50 / 4h	2.18-5.53 mg/l (rat)
	NOEL	220 mg/m3 (rat)
	NOAEL	980 mg/m3 (rat)

**64742-65-0 Distillates (petroleum), solvent-dewaxed heavy paraffinic**

Oral	LD50	5,000 mg/kg (rat)
Dermal	LOAEL	125 mg/kg/24h (rat)
	LD50	2,000-5,000 mg/kg (rabbit)
	NOAEL	150 mg/kg/24h (mouse) 30-2,000 mg/kg/24h (rat)
Inhalative		1,000 mg/kg/24h (rabbit)
	LOAEL	100 mg/kg/24h (mouse)
	LC50 / 4h	2.18-5.53 mg/l (rat)
	NOEL	220 mg/m3 (rat)
	NOAEL	980 mg/m3 (rat)

**128-39-2 2,6-di-tert-butylphenol**

Oral	LD50	5,000 mg/kg (rat)
	NOEL	15 mg/kg/24h (rat)
	NOAEL	100 mg/kg/24h (rat)

- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **11.2 Information on other hazards**

**· Endocrine disrupting properties**

540-97-6	Dodecamethylcyclohexasiloxane	List II
541-02-6	2,2,4,4,6,6,8,8,10,10-decamethylcyclopentasiloxane	List II
556-67-2	octamethylcyclotetrasiloxane	List II; III

## SECTION 12: Ecological information

**· 12.1 Toxicity**
**· Aquatic toxicity:**

<b>64742-54-7 Distillates (petroleum), hydrotreated heavy paraffinic</b>		
LL50	10,000 mg/l/96h (aquatic invertebrates)	
	100 mg/l/96h (fish)	
LL50	10,000 mg/l/72h (aquatic invertebrates)	
LL50	10,000 mg/l/48h (aquatic invertebrates)	

(Contd. on page 7)

**Safety data sheet**  
according to 1907/2006/EC, Article 31



Printing date 30.10.2023

Version number 3.1 (replaces version 3.0)

Revision: 30.10.2023

**Trade name: POWER SYNT 4T SAE 10W/50 JASO MA2**

(Contd. of page 6)

LL50	10,000 mg/l/24h (aquatic invertebrates)
EL50	10,000 mg/l/48h (aquatic invertebrates)
<b>64742-65-0 Distillates (petroleum), solvent-dewaxed heavy paraffinic</b>	
LL50	10,000 mg/l/96h (aquatic invertebrates)
	100 mg/l/96h (fish)
LL50	10,000 mg/l/72h (aquatic invertebrates)
LL50	10,000 mg/l/48h (aquatic invertebrates)
LL50	10,000 mg/l/24h (aquatic invertebrates)
EL50	10,000 mg/l/48h (aquatic invertebrates)
<b>128-39-2 2,6-di-tert-butylphenol</b>	
LC50	1.4 mg/l/96h (fish)
LC50	0.23 mg/l/21d (aquatic invertebrates)
LC50	0.45 mg/l/48h (aquatic invertebrates)
LC50	1 mg/l/14d (fish)
LC50	1.1 mg/l/7d (fish)
LC50	0.59 mg/l/24h (aquatic invertebrates)
EC50	1.7-2.3 mg/l/24h (algae / cyanobacteria)
EC50	1.2-3.9 mg/l/96h (algae / cyanobacteria)
EC50	1.4-3.6 mg/l/72h (algae / cyanobacteria)
EC50	0.14 mg/l/21d (aquatic invertebrates)
EC50	1.7-3.5 mg/l/48h (algae / cyanobacteria)
NOEC	0.035 mg/l/21d (aquatic invertebrates)
NOEC	0.64-2.1 mg/l/96h (algae / cyanobacteria)
NOEC	0.3 mg/l/14d (fish)
LOEC	0.086 mg/kg/28d (aquatic invertebrates)

· **12.2 Persistence and degradability** No further relevant information available.

· **12.3 Bioaccumulative potential**

<b>64742-54-7 Distillates (petroleum), hydrotreated heavy paraffinic</b>	
Partition coefficient	>6 [---] (log Kow) (Bioaccumulation)
<b>64742-65-0 Distillates (petroleum), solvent-dewaxed heavy paraffinic</b>	
Partition coefficient	>6 [---] (log Kow) (Bioaccumulation)
<b>128-39-2 2,6-di-tert-butylphenol</b>	
Partition coefficient	4.48-4.92 [---] (log Kow) (Bioaccumulation)
Biodegradability	<50 % (28d) (Biodegradability) (BIOWIN v4.10)

· **12.4 Mobility in soil** No further relevant information available.

· **12.5 Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **12.6 Endocrine disrupting properties**

For information on endocrine disrupting properties see section 11.

· **12.7 Other adverse effects**

· **Remark:** Harmful to fish

· **Additional ecological information:**

· **General notes:**

Water hazard class 1 (according to Appendix 1 AwSV): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

(Contd. on page 8)

# Safety data sheet

according to 1907/2006/EC, Article 31



Printing date 30.10.2023

Version number 3.1 (replaces version 3.0)

Revision: 30.10.2023

**Trade name: POWER SYNT 4T SAE 10W/50 JASO MA2**

Harmful to aquatic organisms

(Contd. of page 7)

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Contact waste processors for recycling information.

Return product and/or partially emptied container in original packaging to the point of sale or hand it over to a collection point for special waste.

#### Uncleaned packaging:

**Recommendation:** Disposal must be made according to official regulations.

## SECTION 14: Transport information

### 14.1 UN number or ID number

ADR/RID/ADN, ADN, IMDG, IATA

Not classified as hazardous for transport

### 14.2 UN proper shipping name

ADR/RID/ADN, ADN, IMDG, IATA

Not classified as hazardous for transport

### 14.3 Transport hazard class(es)

ADR/RID/ADN, ADN, IMDG, IATA

Class

Not classified as hazardous for transport

### 14.4 Packing group

ADR/RID/ADN, IMDG, IATA

Not classified as hazardous for transport

### 14.5 Environmental hazards:

Not applicable.

### 14.6 Special precautions for user

Not applicable.

### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable.

### UN "Model Regulation":

Not classified as hazardous for transport

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Poisons Act

#### Regulated explosives precursors

None of the ingredients is listed.

#### Regulated poisons

None of the ingredients is listed.

#### Reportable explosives precursors

None of the ingredients is listed.

#### Reportable poisons

None of the ingredients is listed.

#### Directive 2012/18/EU

**Named dangerous substances - ANNEX I** None of the ingredients is listed.

(Contd. on page 9)



**Trade name: POWER SYNT 4T SAE 10W/50 JASO MA2**

(Contd. of page 8)

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has been carried out.

### **SECTION 16: Other information**

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. The classification of the mixture was carried out by calculation in accordance with the rules laid down in Annex I of Regulation (EC) No 1272/2008.*

*No special training instructions to ensure protection of human health and environment are required.*

· **purity requirement**

· **Relevant phrases**

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

· **Department issuing SDS:** Abteilung Produktsicherheit

· **Abbreviations and acronyms:**

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· **\* Data compared to the previous version altered.**

### **Annex: Exposure scenario 1**

· **Short title of the exposure scenario**

*Industrial use of lubricants and greases in vehicles or machinery*

· **Sector of Use**

*SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites*

· **Product category**

*PC16 Heat transfer fluids*

*PC17 Hydraulic fluids*

*PC24 Lubricants, greases, release products*

· **Process category**

*PROC1 Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.*

*PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions*

*PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities*

*PROC9 Transfer of substance or mixture into small containers (dedicated filling line, including weighing)*

· **Environmental release category**

*ERC4 Use of non-reactive processing aid at industrial site (no inclusion into or onto article)*

*ERC7 Use of functional fluid at industrial site*

· **Description of the activities / processes covered in the Exposure Scenario**

*See section 1 of the annex to the Safety Data Sheet.*

· **Conditions of use**

· **Duration and frequency** 5 workdays/week.

· **Physical parameters**

· **Physical state** Fluid

(Contd. on page 10)

**Safety data sheet**  
according to 1907/2006/EC, Article 31



Printing date 30.10.2023

Version number 3.1 (replaces version 3.0)

Revision: 30.10.2023

**Trade name: POWER SYNT 4T SAE 10W/50 JASO MA2**

(Contd. of page 9)

- **Concentration of the substance in the mixture** *The substance is main component.*
- **Other operational conditions**
- **Other operational conditions affecting environmental exposure** *No special measures required.*
- **Other operational conditions affecting consumer exposure** *Not required.*
- **Other operational conditions affecting consumer exposure during the use of the product** *Not applicable.*
- **Risk management measures**
- **Worker protection**
- **Organisational protective measures** *No special measures required.*
- **Technical protective measures** *No special measures required.*
- **Personal protective measures** *No special measures required.*
- **Measures for consumer protection** *No special measures required.*
- **Environmental protection measures**
- **Air** *No special measures required.*
- **Water** *No special measures required.*
- **Disposal measures**  
*Disposal must be made according to official regulations.*  
*Ensure that waste is collected and contained.*
- **Disposal procedures** *Dispose of product residues with household waste.*
- **Waste type** *Partially emptied and uncleaned packaging*
- **Exposure estimation**
- **Consumer** *Not relevant for this Exposure Scenario.*
- **Guidance for downstream users** *No further relevant information available.*

## Annex: Exposure scenario 2

- **Short title of the exposure scenario**  
*Professional use of lubricants and greases in vehicles or machines*
- **Sector of Use**  
*SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)*
- **Product category**  
*PC16 Heat transfer fluids*  
*PC17 Hydraulic fluids*  
*PC24 Lubricants, greases, release products*
- **Process category**  
*PROC1 Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.*  
*PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions*  
*PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities*  
*PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities*  
*PROC20 Use of functional fluids in small devices*
- **Environmental release category**  
*ERC9a Widespread use of functional fluid (indoor)*  
*ERC9b Widespread use of functional fluid (outdoor)*
- **Description of the activities / processes covered in the Exposure Scenario**  
*See section 1 of the annex to the Safety Data Sheet.*
- **Conditions of use**
- **Duration and frequency** *5 workdays/week.*
- **Physical parameters**
- **Physical state** *Fluid*
- **Concentration of the substance in the mixture** *The substance is main component.*
- **Other operational conditions**
- **Other operational conditions affecting environmental exposure** *No special measures required.*
- **Other operational conditions affecting consumer exposure** *Not required.*

(Contd. on page 11)

# Safety data sheet

according to 1907/2006/EC, Article 31



Printing date 30.10.2023

Version number 3.1 (replaces version 3.0)

Revision: 30.10.2023

**Trade name: POWER SYNT 4T SAE 10W/50 JASO MA2**

(Contd. of page 10)

- **Other operational conditions affecting consumer exposure during the use of the product**  
Not applicable.
- **Risk management measures**
- **Worker protection**
- **Organisational protective measures** No special measures required.
- **Technical protective measures** No special measures required.
- **Personal protective measures** No special measures required.
- **Measures for consumer protection** No special measures required.
- **Environmental protection measures**
- **Air** No special measures required.
- **Water** No special measures required.
- **Disposal measures**  
Disposal must be made according to official regulations.  
Ensure that waste is collected and contained.
- **Disposal procedures** Dispose of product residues with household waste.
- **Waste type** Partially emptied and uncleaned packaging
- **Exposure estimation**
- **Consumer** Not relevant for this Exposure Scenario.
- **Guidance for downstream users** No further relevant information available.

## Annex: Exposure scenario 3

- **Short title of the exposure scenario** Private use of lubricants and greases in vehicles or machines
- **Sector of Use** SU21 Consumer uses: Private households / general public / consumers
- **Product category** PC24 Lubricants, greases, release products
- **Environmental release category**  
ERC9a Widespread use of functional fluid (indoor)  
ERC9b Widespread use of functional fluid (outdoor)
- **Description of the activities / processes covered in the Exposure Scenario**  
See section 1 of the annex to the Safety Data Sheet.
- **Conditions of use**
- **Duration and frequency** 5 workdays/week.
- **Physical parameters**
- **Physical state** Fluid
- **Concentration of the substance in the mixture** The substance is main component.
- **Other operational conditions**
- **Other operational conditions affecting environmental exposure** No special measures required.
- **Other operational conditions affecting consumer exposure** Not required.
- **Other operational conditions affecting consumer exposure during the use of the product**  
Not applicable.
- **Risk management measures**
- **Worker protection**
- **Organisational protective measures** No special measures required.
- **Technical protective measures** No special measures required.
- **Personal protective measures** No special measures required.
- **Measures for consumer protection** No special measures required.
- **Environmental protection measures**
- **Air** No special measures required.
- **Water** No special measures required.
- **Disposal measures**  
Disposal must be made according to official regulations.  
Ensure that waste is collected and contained.
- **Disposal procedures** Dispose of product residues with household waste.
- **Waste type** Partially emptied and uncleaned packaging
- **Exposure estimation**
- **Consumer** Not relevant for this Exposure Scenario.
- **Guidance for downstream users** No further relevant information available.