

ATV QUAD 4T SAE 10W/40 MA2

High-quality synthetic motor oil for four-stroke ATVs/Quads

Description

MOTOREX ATV QUAD 4T is a modern, synthetic blend motor oil for ATVs/Quads. This oil offers a good level of shear stability and a short lubrication rise time, even at low temperatures. JASO MA2 approval guarantees the fault-free functioning of wet multi-disc clutches.

Product features

- outstanding wear protection
- excellent cold-starting properties
- high shear stability

Field of application

MOTOREX ATV QUAD 4T SAE 10W/40 is formulated for tough conditions in the four-stroke engines of ATVs (all-terrain vehicles) and Quads. Meets the requirements of the manufacturer's specifications.

Specifications

API SG, API SH, API SJ, API SL, JASO MA2

Technical Data

Properties	Test according to	Unit	Values
Colour			yellowish-brown
Viscosity			SAE 10W/40
Density at 20 °C		g/cm ³	0.866
Viscosity at 40°C	DIN 51562-1	mm ² /s	85.8
Viscosity at 100°C	DIN 51562-1	mm ² /s	13.2
Viscosity index	DIN ISO 2909		154.0
Visco. according HTHS at 150°C	CEC-L-36 A-97	mPa.s	>= 3.5
Flash point	DIN EN ISO 2592	°C	>= 200
Pourpoint	ASTM D5950	°C	-36
NOACK	CEC L-40-A-93	Percentage	9.10 %
Sulphate residue content	DIN EN ISO 6245	Percentage	0.80 %
TBN	DIN ISO 3771	mg KOH/g	5.70 mgKOHg

The above information corresponds to the current state of our knowledge. We reserve the right to make changes. The performance characteristics indicated are based on testing and production tolerances standard in this industry. A safety data sheet is available.