



MOTO GEAR OIL

SAE 10W/30

Multi-grade gear oil for motorcycles

Description

MOTO GEAR OIL SAE 10W/30 is a synthetically based, multi-grade gear oil, which is specially tuned to the needs of motorcycles. Top class base oils and the latest additives ensure optimum lubrication and gear change.

Advantages

- excellent gear changing at all temperatures
- first class anti-corrosion
- exceptional anti-foaming
- optimum lubrication throughout the life of the oil

Field of application

MOTO GEAR OIL SAE 10W/30 is particularly suitable for gearboxes of 2-stroke motor-cycles, which are fitted with oil bath clutch, as well as for all motorcycles with separate gearbox lubrication.

Specifications

API GL-4, complies with SAE 80W/85

Technical data

Properties	Unit	Test according to	Values
Viscosity-Class		SAE J 300	10W/30 (= 80W/85)
Colour		DIN ISO 2049	brown
Density at 20 °C	g/ml	ASTM D 4052	0.868
Viscosity at 40 °C	mm ² /s	DIN 51562-1	76
Viscosity at 100 °C	mm ² /s	DIN 51562-1	11.7
Viscosity index		DIN ISO 2909	148
Pourpoint	°C	ASTM D 5950	-30
Flashpoint	°C	DIN EN ISO 2592	>200

Water hazard class: WGK 1
Waste code: EWC 130 205

The above information is subject to change without prior notice, although it is in accordance with current standards. Performance characteristics indicated are based on usual tolerances which occur during measuring and production using the latest technology. A safety data sheet is available.

