

Thank you for purchasing a National Cycle product. Read these instructions carefully and thoroughly before beginning work. Dealers, if installing this windshield for a customer, please give them this manual upon completion. It contains information needed to properly maintain and use this product.

PARTS LIST

ITEM	DESCRIPTION	QUANTITY
A	VStream Windscreen, 4.0mm Quantum® Hardcoated Polycarbonate	1

TOOLS REQUIRED:
 #2 or #3 Philips
 Screwdriver



PREPARATION

Carefully unpack your new windscreen and make sure you have the tools required for installation.

 **Retain all OEM fasteners, as they will be reused.**

INSTALLATION


Step 1


Using a Phillips screwdriver, simply loosen (do not remove) the four mounting screws on the stock windscreen. Remove the stock screen and set it aside.

Step 2

Position the new VStream Windscreen on the fairing over the original mount points. Securely tighten the four original mounting screws.

That's all there is to it.



 **NOTE:** The Wellnuts for the windscreen in the FLTR's fairing are perpendicular to the curvature of the fairing. If they are removed, be careful reinstalling the mounting screws to avoid cross-threading them.



Ask for Shield Wash™ and RainZip® at your local dealer or visit www.nationalcycle.com.

CLEANING AND MAINTENANCE

To clean your windshield, wash with a clean soft cloth and plenty of warm water and, if necessary, a non-abrasive soap such as dishwashing liquid. Flannel or soft cham-
ois make good cleaning cloths. **Paint, glue residue or grease removal:** Moisten cot-
 ton wad with naphtha or turpentine followed by a wash as above.

National Cycle **Shield Wash™** (N1401-01) makes a good daily cleaner and comes with a handy travel-size bottle. Shield Wash is safe for all windshields and helmet visors.

Do not clean polycarbonate in hot sun or high temperatures. Do not clean the screen with household glass cleaners.

Do not allow brake fluid, alcohol, or strong solvents to contact the windshield.

RAIN REPELLENT

Do not use rain protective products made for glass. We recommend National Cycle's **RainZip®** (N1410-01) to keep your windshield clear in rainy weather.



National Cycle 3-Year Limited Warranty

Register Your Windshield Online at www.nationalcycle.com

National Cycle hereby warrants to the original registered owner of a National Cycle polycarbonate windshield for a period of three years from the date of purchase against breakage. This limited warranty is expressly limited to the replacement of the polycarbonate windscreen. This limited warranty does not include scratches, coating failure, cosmetic wear and tear, replacement of hardware, or any consequential damages or expenses including labor cost of installation, removal and/or replacement, inconvenience, inbound freight expenses or damage to any other component of the vehicle or any other accessories. Certain chemicals, generally known as acidic hydrocarbons, are known to cause polycarbonate damage and will not be covered under this limited warranty. Please refer to the cleaning instructions supplied with all National Cycle windshields. Visit www.nationalcycle.com for further details or call or write National Cycle Inc.

⚠ WARNING

Never operate your motorcycle with loose accessory mounting hardware. Check the hardware for tightness regularly.

Motorcycles are built with enough frame rigidity to withstand the moderate loads imposed on them by the foreseeable addition of an accessory(ies). If an accessory(ies) adversely affects your motorcycle's stability, immediately remove the accessory(ies). Do not operate a motorcycle that exhibits unsafe handling traits.

Have experienced service personnel correct any problem before riding with the accessory(ies) installed. For further questions concerning handling problems associated with an accessory(ies), contact your dealer, motorcycle manufacturer, or accessory manufacturer.

Sunlight reflected off the inside curvature of the windshield can, at certain times of the day, cause extreme heat buildup on the motorcycle's instruments and possibly even melt them. Exercise care in parking to avoid this. Park your motorcycle facing the sun, or place an opaque object over the instruments and dash panel.



You May Also Like:

N5200 Heat Shields

Our dark tint Quantum® hardcoated polycarbonate Heat Shields allow the beauty of your engine to shine through while blocking the radiating heat. National Cycle Heat Shields are available through your local dealer or visit our web site.