



BIKE GREASE 2000

NLGI 2

Long-life grease

Description

High-performance, long-lasting grease based on calcium for optimum lubrication. Maximum adhesive power and absolute resistance to water. Optimum corrosion and wear protection even under extreme loads. Excellent pressure absorption capacity. Increases the duration of lubrication intervals.

Advantages

- Ideal for joints, hubs and headsets
- No display stands required. Tube stands by itself
- Design for the bicycle and motorbike sectors
- Excellent pressure resistance
- Extremely water-repellent
- Easy to apply thanks to integrated brush
- QR code on the label for more product details
- carbon tested

Field of application

Ideal for lubricating bearings, wheel bearings, joints and headsets.

Notes

Neutral in contact with elastomers and seals and prevents galvanic corrosion

Technical data

Properties	Unit	Test according to	Values
Colour			fluorescent yellow-green
Density at 20 °C	g/cm ³	ASTM D4052	0.930
Viscosity at 40 °C	mm ² /s	DIN 51562-1	800
Base oil type			mineral
Corrosion test to EMCOR		DIN 51802	0-0
Corrosion test on copper		DIN 51811	1
Temperature operating range	24h/100°C		-30 bis 120
Drop point	°C	DIN ISO 2176	>140
Thickener			Ca-12-OH
Water resistance		DIN 51807-1	0-90
VKA welding load	N	DIN 51350-4	2400
Worked penetration	0.1 mm	DIN ISO 2137	265 - 295

European waste catalogue: 12 01 12 / Water hazard class: 1

The above information corresponds to the current state of our knowledge. We reserve the right to make changes. The performance characteristics indicated are based on testing and production tolerances standard in this industry. A safety data sheet is available.



BUCHER AG LANGENTHAL
 MOTOREX-Schmiertechnik
 Postfach, CH-4901 Langenthal, Schweiz
 Tel. +41 (0)62 919 75 75, Fax +41 (0)62 919 75 95
 info@motorex.com, www.motorex.com

MOTOREX AG LANGENTHAL
 Industrie-Schmiertechnik
 Postfach, CH-4901 Langenthal, Schweiz
 Tel. +41 (0)62 919 74 74, Fax +41 (0)62 919 76 96
 info@motorex.com, www.motorex.com