

Safety data sheet
according to (EU) 2015/830

Printing date 21.12.2015

Version number 1

Revision: 21.12.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name: CARBURETOR SPRAY**
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture**
Carburetor cleaner
Only for proper handling.
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
BUCHER_AG_LANGENTHAL
MOTOREX-Schmiertechnik
Bern-Zürich-Strasse_31__
CH-4901_Langenthal__
Telefon_+41_(0)62_919_75_75
- **Further information obtainable from: msds@motorex.com**
- **1.4 Emergency telephone number:**
Toxicological Information Centre, CH-8028 Zurich,
info@toxi.ch,
T. +41 (0) 44 251 51 51

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Aerosol 1 H222-H229 *Extremely flammable aerosol. Pressurised container: May burst if heated.*



GHS08 health hazard

Repr. 2 H361d *Suspected of damaging the unborn child.*



GHS07

Eye Irrit. 2 H319 *Causes serious eye irritation.*

Aquatic Chronic 3 H412 *Harmful to aquatic life with long lasting effects.*

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

Safety data sheet

according to (EU) 2015/830

Printing date 21.12.2015

Version number 1

Revision: 21.12.2015

Trade name: **CARBURETOR SPRAY**

(Contd. of page 1)

- **Hazard pictograms**



GHS02 GHS07 GHS08

- **Signal word** *Danger*

- **Hazard-determining components of labelling:**

toluene

- **Hazard statements**

H222-H229 *Extremely flammable aerosol. Pressurised container: May burst if heated.*H319 *Causes serious eye irritation.*H361d *Suspected of damaging the unborn child.*H412 *Harmful to aquatic life with long lasting effects.*

- **Precautionary statements**

P101 *If medical advice is needed, have product container or label at hand.*P102 *Keep out of reach of children.*P103 *Read label before use.*P210 *Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.*P251 *Do not pierce or burn, even after use.*P211 *Do not spray on an open flame or other ignition source.*P280 *Wear protective gloves/protective clothing/eye protection/face protection.*P273 *Avoid release to the environment.*P305+P351+P338 *IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.*P308+P313 *IF exposed or concerned: Get medical advice/attention.*P405 *Store locked up.*P410+P412 *Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.*P501 *Dispose of contents/container in accordance with local/regional/national/international regulations.*

- **2.3 Other hazards**

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- **3.2 Chemical characterisation: Mixtures**

- **Description:** Mixture of substances listed below with nonhazardous additions.

- **Dangerous components:**

CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32	butane ⚠ Flam. Gas 1, H220; Press. Gas C, H280	25-50%
EC number: 919-446-0 Reg.nr.: 01-2119458049-33	Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) ⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ STOT SE 3, H336	10-25%

(Contd. on page 3)

Safety data sheet according to (EU) 2015/830

Printing date 21.12.2015

Version number 1

Revision: 21.12.2015

Trade name: CARBURETOR SPRAY

(Contd. of page 2)		
CAS: 67-63-0 EINECS: 200-661-7 Reg.nr.: 01-2119457558-25	propan-2-ol ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	10-25%
CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2119471330-49	acetone ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	10-25%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21	propane ⚠ Flam. Gas 1, H220; Press. Gas C, H280	5-10%
CAS: 108-88-3 EINECS: 203-625-9 Reg.nr.: 01-2119471310-51	toluene ⚠ Flam. Liq. 2, H225; ⚠ Repr. 2, H361d; STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Skin Irrit. 2, H315; STOT SE 3, H336	5-10%
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27	isobutane ⚠ Flam. Gas 1, H220; Flam. Liq. 1, H224; Press. Gas C, H280	1-2.5%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:**
Remove residues with soap and water.
Remove contaminated clothing immediately.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**
No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.

(Contd. on page 4)

Safety data sheet according to (EU) 2015/830

Printing date 21.12.2015

Version number 1

Revision: 21.12.2015

Trade name: CARBURETOR SPRAY

(Contd. of page 3)

- Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
 - **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.
Do not spray onto a naked flame or any incandescent material.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Store in a cool location.
Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep container tightly sealed.
Do not seal receptacle gas tight.
Store in cool, dry conditions in well sealed receptacles.
Protect from heat and direct sunlight.
- **Storage class:** 2 B
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

106-97-8 butane	
WEL	Short-term value: 1810 mg/m ³ , 750 ppm Long-term value: 1450 mg/m ³ , 600 ppm Carc (if more than 0.1% of buta-1.3-diene)
67-63-0 propan-2-ol	
WEL	Short-term value: 1250 mg/m ³ , 500 ppm Long-term value: 999 mg/m ³ , 400 ppm
67-64-1 acetone	
WEL	Short-term value: 3620 mg/m ³ , 1500 ppm Long-term value: 1210 mg/m ³ , 500 ppm

(Contd. on page 5)

Safety data sheet according to (EU) 2015/830

Printing date 21.12.2015

Version number 1

Revision: 21.12.2015

Trade name: **CARBURETOR SPRAY**

(Contd. of page 4)

108-88-3 toluene

WEL	Short-term value: 384 mg/m ³ , 100 ppm Long-term value: 191 mg/m ³ , 50 ppm Sk
-----	--

- **Additional information:** The lists valid during the making were used as basis.
- **8.2 Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
Avoid contact with the eyes.
Avoid contact with the eyes and skin.
- **Respiratory protection:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:**



Tightly sealed goggles

SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**
- **General Information**
- **Appearance:**

Form:	Liquefied gas
Colour:	Colourless
Odour:	Solvent-like
Odour threshold:	Not determined.

(Contd. on page 6)

GB

Safety data sheet according to (EU) 2015/830

Printing date 21.12.2015

Version number 1

Revision: 21.12.2015

Trade name: CARBURETOR SPRAY

(Contd. of page 5)

· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	-42 °C (DIN EN ISO 3405)
· Flash point:	< -40 °C
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	365 °C (DIN 51794)
· Decomposition temperature:	Not determined.
· Self-igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	1.5 Vol %
Upper:	13.0 Vol %
· Vapour pressure at 20 °C:	2100 hPa
· Density at 20 °C:	0.697 g/cm ³ (ASTM D 4052)
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not applicable.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	<1 mm ² /s @ 40 °C (DIN 51562-1)
VOC (EC)	88.00 %
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

(Contd. on page 7)

Safety data sheet according to (EU) 2015/830

Printing date 21.12.2015

Version number 1

Revision: 21.12.2015

Trade name: CARBURETOR SPRAY

(Contd. of page 6)

LD/LC50 values relevant for classification:
108-88-3 toluene

Oral	LD50	5000 mg/kg (rat)
Dermal	LD50	12124 mg/kg (rabbit)
Inhalative	LC50/4 h	5320 mg/l (mouse)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation**
Causes serious eye irritation.
- **Respiratory or skin sensitisation**
Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity**
Suspected of damaging the unborn child.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) (Self-classification according VwVwS, 17.05.1999): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
Harmful to aquatic organisms
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.

European waste catalogue

16 05 04*	gases in pressure containers (including halons) containing hazardous substances
-----------	---

(Contd. on page 8)

GB

Safety data sheet according to (EU) 2015/830

Printing date 21.12.2015

Version number 1



Revision: 21.12.2015

Trade name: CARBURETOR SPRAY

(Contd. of page 7)

- **Uncleaned packaging:**
- **Recommendation:**
Disposal must be made according to official regulations.
Discharged containers can contain flammable or explosive vapours.

SECTION 14: Transport information

<ul style="list-style-type: none"> · 14.1 UN-Number · ADR,ADN, IMDG, IATA 	UN1950	
<ul style="list-style-type: none"> · 14.2 UN proper shipping name · ADR/ADN · IMDG · IATA 	1950 AEROSOLS AEROSOLS Aerosols, flammable	
<ul style="list-style-type: none"> · 14.3 Transport hazard class(es) · ADR/ADN 	<div style="text-align: center;">  </div> <ul style="list-style-type: none"> · Class · Label 	2 5F Gases. 2.1
<ul style="list-style-type: none"> · IMDG, IATA 	<div style="text-align: center;">  </div> <ul style="list-style-type: none"> · Class · Label 	2.1 2.1
<ul style="list-style-type: none"> · 14.4 Packing group · ADR,ADN, IMDG, IATA 	Void	
<ul style="list-style-type: none"> · 14.5 Environmental hazards: · Marine pollutant: 	Yes	
<ul style="list-style-type: none"> · 14.6 Special precautions for user · Danger code (Kemler): · EMS Number: · Stowage Code 	Warning: Gases. - F-D,S-U SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.	

(Contd. on page 9)

GB

Safety data sheet according to (EU) 2015/830

Printing date 21.12.2015

Version number 1

Revision: 21.12.2015

Trade name: **CARBURETOR SPRAY**

(Contd. of page 8)

· Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR/ADN · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E0 Not permitted as Excepted Quantity
· Transport category · Tunnel restriction code	2 D
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E0 Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category P3a** FLAMMABLE AEROSOLS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **15.2 Chemical safety assessment:**
A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
- H220 Extremely flammable gas.
- H224 Extremely flammable liquid and vapour.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.

(Contd. on page 10)

Safety data sheet
according to (EU) 2015/830

Printing date 21.12.2015

Version number 1

Revision: 21.12.2015

Trade name: CARBURETOR SPRAY

(Contd. of page 9)

H336 May cause drowsiness or dizziness.
H361d Suspected of damaging the unborn child.
H373 May cause damage to organs through prolonged or repeated exposure.
H411 Toxic to aquatic life with long lasting effects.

· **Department issuing MSDS:** Abteilung Produktsicherheit

· **Abbreviations and acronyms:**

Flam. Gas 1: Flammable gases, Hazard Category 1

Aerosol 1: Flammable aerosols, Hazard Category 1

Press. Gas C: Gases under pressure: Compressed gas

Flam. Liq. 1: Flammable liquids, Hazard Category 1

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Flam. Liq. 3: Flammable liquids, Hazard Category 3

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

Repr. 2: Reproductive toxicity, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2

Asp. Tox. 1: Aspiration hazard, Hazard Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3

GB