

Printing date 12.08.2019 Version number 2.0 Revision: 12.08.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: CHAINLUBE ADVENTURE SPRAY
- · UFI: Q9N0-70M9-E003-0FH2
- 1.2 Relevant identified uses of the substance or mixture and uses advised against

Professional use of lubricants and greases in open systems

Professional use of lubricants and greases in open systems

Industrial use of lubricants and greases in vehicles or machinery

According to the generic exposure scenarios of the ATIEL / ATC on the use of lubricants

(V1.0, 07.01.2013)

See details of exposure scenarios in Annex

· Application of the substance / the mixture

Only for proper handling.

Chain lubricant

- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

BUCHER AG LANGENTHAL MOTOREX-Schmiertechnik Bern-Zürich-Strasse 31 CH-4901 Langenthal Telefon +41 (0)62 919 75 75

· Only representative in EU:

MOTOREX GmbH, Industrie Schmiertechnik, Bismarckstrasse 28, D-69198 Schriesheim

- · Further information obtainable from: msds@motorex.com
- 1.4 Emergency telephone number:

In case of a medical emergency following exposure to a chemical, the public should call NHS Direct in England or Wales 0845 46 47 or NHS 24 in Scotland 08454 24 24 24 (UK only).

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May

burst if heated.

Skin Irrit. 2 H315 Causes skin irritation.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02 GHS07

· Signal word Danger

(Contd. on page 2)

Printing date 12.08.2019 Version number 2.0 Revision: 12.08.2019

Trade name: CHAINLUBE ADVENTURE SPRAY

(Contd. of page 1)

· Hazard-determining components of labelling:

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

Hydrocarbons C6-C7, n-alkanes, iso-alkanes, cyclenes, <5% n-hexane

Hydrocarbons, C15-C20 n-alkanes, isoalkanes, cycloalkanes, <0.03% aromatics Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics

Hydrocarbons, C13-C16, n-alkanes, isoalkanes, cycloalkanes, <12:03% aromatics isopentane

Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H315 Causes skin irritation.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P264 Wash thoroughly after handling.

P273 Avoid release to the environment.

P280 Wear protective gloves.

P332+P313 If skin irritation occurs: Get medical advice/attention.

P362+P364 Take off contaminated clothing and wash it before reuse.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· Additional information:

Buildup of explosive mixtures possible without sufficient ventilation.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- PBT: Not applicable.
- · **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · **Description**: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0	butane Flam. Gas 1, H220; Press. Gas (Comp.), H280	10-25%
Reg.nr.: 01-2119474691-32 EC number: 920-750-0	Hydrocarbons, C7-C9, n-alkanes, isoalkanes,	>10-<20%
Reg.nr.: 01-2119473851-33	cyclics	210-12070
	Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H336	

(Contd. on page 3

Printing date 12.08.2019 Version number 2.0 Revision: 12.08.2019

Trade name: CHAINLUBE ADVENTURE SPRAY

EC number: 921-024-6 Reg.nr.: 01-2119475514-35	Hydrocarbons C6-C7, n-alkanes, iso-alkanes, cyclenes, <5% n-hexane Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336	ontd. of page 2) ≥10-<20%
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21	propane Flam. Gas 1, H220; Press. Gas (Comp.), H280	2.5-7.5%
Regulation (EC) No 648/200 aliphatic hydrocarbons	4 on detergents / Labelling for contents	≥5 - <15%

[·] Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Remove residues with soap and water.

Immediately wash with water and soap and rinse thoroughly.

- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed**No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- · 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 4)

Printing date 12.08.2019 Version number 2.0 Revision: 12.08.2019

Trade name: CHAINLUBE ADVENTURE SPRAY

See Section 13 for disposal information.

(Contd. of page 3)

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling No special precautions are necessary if used correctly.
- Information about fire and explosion protection:

Keep ignition sources away - Do not smoke.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use. Do not spray onto a naked flame or any incandescent material.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 2 B
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see section 7.
- · 8.1 Control parameters

· Ingre	Ingredients with limit values that require monitoring at the workplace: 106-97-8 butane		
106-9			
WEL	Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)		

Car	c (if more than 0.1% of buta-1.3-diene)	
DNELs		
Hydrocar	bons, C7-C9, n-alkanes, isoalkanes, c	yclics
Oral	DNEL/general population/Systemic effects/Long-term	699 mg/kg/24h (consumer)
Dermal	DNEL / Workers / Systemic effects / Long-term	773 mg/kg/24h (worker)
	DNEL/general population/Systemic effects/Long-term	699 mg/kg/24h (consumer)
Inhalative	DNEL / Workers / Systemic effects / Long-term	2,035 mg/m3 (worker)
	DNEL/general population/Systemic effects/Long-term	608 mg/m3 (consumer)
Hydrocar	bons C6-C7, n-alkanes, iso-alkanes, c	cyclenes, <5% n-hexane
Oral	DNEL/general population/Systemic effects/Long-term	699 mg/kg/24h (consumer)
Dermal	DNEL / Workers / Systemic effects / Long-term	773 mg/kg/24h (worker)
	DNEL/general population/Systemic effects/Long-term	699 mg/kg/24h (consumer)
	1	(Contd. on page

Printing date 12.08.2019 Version number 2.0 Revision: 12.08.2019

Trade name: CHAINLUBE ADVENTURE SPRAY

			(Contd. of page 4)
Inhalative	DNEL / Workers / Systemic effects /	2,035 mg/m3 (worker)	
	Long-term	, ,	
	DNEL/general population/Systemic effects/Long-term	608 mg/m3 (consumer)	

- Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

Respiratory protection:

Not necessary if room is well-ventilated.

Respiratory protection if formation of aerosol or mist: use mask with filter type A2, A2/P2 or ABEK.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Protective gloves to EN374, resistant to oil in use. Standard EN 374 Level 3 control G1 The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Fluorocarbon rubber (Viton)

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.4 mm

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the mixture of chemicals mentioned below the penetration time has to be at least 60 minutes (Permeation according to EN 374 Part 3: Level 1).

- · Eye protection: Not required.
- Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Colour: Liquefied gas Beige

· Odour:

Solvent-like

· Odour threshold:

Not determined.

(Contd. on page 6)

Printing date 12.08.2019 Version number 2.0 Revision: 12.08.2019

Trade name: CHAINLUBE ADVENTURE SPRAY

	(Contd. of page
pH-value:	Not determined.
Change in condition Melting point/freezing point: Initial boiling point and boiling range	Undetermined. : Not applicable, as aerosol.
Flash point:	<-20 °C
Flammability (solid, gas):	Not applicable.
Ignition temperature:	>230 °C (DIN 51794)
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
Explosion limits: Lower: Upper:	0.9 Vol % 8.5 Vol %
Vapour pressure at 20 °C:	2,100 hPa
Density at 20 °C: Relative density Vapour density Evaporation rate	0.756 g/cm³ (ASTM D 4052) Not determined. Not determined. Not applicable.
Solubility in / Miscibility with water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity: Dynamic: Kinematic:	Not determined. < 50 mm²/s @40 °C (DIN 51562-1)
Solids content: 9.2 Other information	0.0 % No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

(Contd. on page 7)

Printing date 12.08.2019 Version number 2.0 Revision: 12.08.2019

Trade name: CHAINLUBE ADVENTURE SPRAY

		(Contd. of pa
		t for classification:
106-97-8		
Inhalative		1,442.738-1.443 mg/l (rat)
		800,000 ppm (rat)
	LC50 / 2h	1,237 mg/l (mouse)
	LC50 / 2h	520,400-539,600 ppm (mouse)
	LC50 / 4h	658 mg/l (rat)
	NOAEC	4,000-16,000 ppm (rat)
	NOAEC	7.2-21.4 mg/l (rat)
	LOAEC	21.6 mg/l (rat)
	LOAEC	12,000 ppm (rat)
Hydrocar	bons, C7-C9, n	-alkanes, isoalkanes, cyclics
Oral	LD50	8 ml/kg (rat)
Dermal	LD50	4 ml/kg (rat)
	LD50	2,800-3,100 mg/kg (rat)
Inhalative	LC50 / 4h	23.3 mg/l (rat)
	NOAEC	5.8-24.3 mg/l (rat)
Hydrocar	bons C6-C7, n	-alkanes, iso-alkanes, cyclenes, <5% n-hexane
Oral	LD50	8 ml/kg (rat)
Dermal	LD50	4 ml/kg (rat)
	LD50	2,800-3,100 mg/kg (rat)
Inhalative	LC50 / 4h	25.2 mg/l (rat)
	NOAEC	8.117-24.3 mg/l (rat)
74-98-6 p	ropane	
Inhalative	LC50 / 15 min	1,442.738-1.443 mg/l (rat)
	LC50 / 15 min	800,000 ppm (rat)
	LC50 / 2h	1,237 mg/l (mouse)
	LC50 / 2h	520,400-539,600 ppm (mouse)
	NOAEC	4,000-16,000 ppm (rat)
	NOAEC	7.214-21.394 mg/l (rat)
	LOAEC	21.64 mg/l (rat)
	LOAEC	12,000 ppm (rat)

- Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.

(Contd. on page 8)

Printing date 12.08.2019 Version number 2.0 Revision: 12.08.2019

Trade name: CHAINLUBE ADVENTURE SPRAY

(Contd. of page 7) · **Aspiration hazard**May be fatal if swallowed and enters airways.

12.1 Tox Aquatic	toxicity:
-	B butane
LC50	24.1-147.5 mg/l/96h (fish)
LC50	14.2-69.4 mg/l/48h (aquatic invertebrates)
EC50	7.7-19.4 mg/l/96h (algae / cyanobacteria)
Hydroca	arbons, C7-C9, n-alkanes, isoalkanes, cyclics
EC50	0.23 mg/l/21d (aquatic invertebrates)
EC50	0.64 mg/l/48h (aquatic invertebrates)
LL50	3-10 mg/l/96h (fish)
LL50	10-30 mg/l/72h (fish)
LL50	10-30 mg/l/48h (fish)
LL50	30-100 mg/l/24h (fish)
LL0	3 mg/l/96h (fish)
EL50	13 mg/l/96h (algae / cyanobacteria)
EL50	4.6-10 mg/l/48h (aquatic invertebrates)
	10-30 mg/l/48h (algae / cyanobacteria)
EL50	10-22 mg/l/24h (aquatic invertebrates)
	10-30 mg/l/24h (algae / cyanobacteria)
EL50	10-30 mg/l/72h (algae / cyanobacteria)
EL0	4.6 mg/l/48h (aquatic invertebrates)
EL0	10 mg/l/24h (aquatic invertebrates)
NOEC	0.17 mg/l/21d (aquatic invertebrates)
NOELR	0.574 mg/l/28d (fish)
NOELR	1 mg/l/21d (aquatic invertebrates)
NOELR	6.3 mg/l/96h (algae / cyanobacteria)
LOEC	0.32 mg/l/72h (aquatic invertebrates)
	arbons C6-C7, n-alkanes, iso-alkanes, cyclenes, <5% n-hexane
EC50	0.23 mg/l/21d (aquatic invertebrates)
EC50	0.64 mg/l/48h (aquatic invertebrates)
LL50	11.4 mg/l/96h (fish)
LL50	15.8 mg/l/72h (fish)
LL0	5.1 mg/l/96h (fish)
EL50	3 mg/l/48h (aquatic invertebrates)
EL50	12 mg/l/24h (aquatic invertebrates)
EL50	10-100 mg/l/72h (algae / cyanobacteria)
EL0	2 mg/l/48h (aquatic invertebrates)
EL0	10 mg/l/24h (aquatic invertebrates)
NOEC NOELR	0.17 mg/l/21d (aquatic invertebrates)

Printing date 12.08.2019 Version number 2.0 Revision: 12.08.2019

Trade name: CHAINLUBE ADVENTURE SPRAY

		(Contd. of page 8)
NO	ELR	1 mg/l/21d (aquatic invertebrates)
LOE	EC	0.32 mg/l/72h (aquatic invertebrates)
74-9	98-6	propane
LC5	LC50 24.11-147.54 mg/l/96h (fish)	
LC5	LC50 14.22-69.43 mg/l/48h (aquatic invertebrates)	
EC5		7.71-19.37 mg/l/96h (algae / cyanobacteria)

· 12.2 Persistence and degradability No further relevant information available.

12.2 Persistence a	ind degradability No further relevant illiornation available.			
· 12.3 Bioaccumula	tive potential			
106-97-8 butane				
Partition coefficient	1.09-2.8 [] (log Kow) (Bioaccumulation)			
Hydrocarbons, C7	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics			
Biodegradability	Biodegradability 98 % (28d) (Biodegradability) (OECD 301 F)			
Hydrocarbons C6-	C7, n-alkanes, iso-alkanes, cyclenes, <5% n-hexane			
Biodegradability	81 % (28d) (Biodegradability) (OECD 301 F)			
74-98-6 propane				
Partition coefficient	Partition coefficient 1.09-2.8 [] (log Kow) (Bioaccumulation)			

- 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (according to Appendix 1 AWSV): significantly hazardous to water Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Contact waste processors for recycling information.

· European waste catalogue

16 05 04* gases in pressure containers (including halons) containing hazardous substances

- Uncleaned packaging:
- · Recommendation:

Disposal must be made according to official regulations.

Discharged containers can contain flammable or explosive vapours.

GE

(Contd. on page 10)

Printing date 12.08.2019 Version number 2.0 Revision: 12.08.2019

Trade name: CHAINLUBE ADVENTURE SPRAY

(Contd. of page 9)

14.1 UN-Number ADR/RID/ADN, IMDG, IATA	UN1950
14.2 UN proper shipping name ADR/RID/ADN IMDG	1950 AEROSOLS AEROSOLS
IATA	AEROSOLS, flammable
14.3 Transport hazard class(es)	
ADR/RID/ADN	
Class	2 5F Gases.
Label IMDG, IATA	2.1
Class	2.1
Label	2.1
14.4 Packing group ADR/RID/ADN, IMDG, IATA	Void
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user Danger code (Kemler): EMS Number:	Warning: Gases. - F-D,S-U
Stowage Code	SW1 Protected from sources of heat.
Segregation Code	SW22 For AEROSOLS with a maxim capacity of 1 litre: Category A. I AEROSOLS with a capacity above 1 li Category B. For WASTE AEROSOL Category C, Clear of living quarters. SG69 For AEROSOLS with a maxim capacity of 1 litre: Segregation as for class 9. Stow "separa from" class 1 except for division 1.4. For AEROSOLS with a capacity abov litre: Segregation as for the approprisubdivision of class 2. For WASTE AEROSOLS:
	Segregation as for the appropriation of class 2.

(Contd. on page 11)

Printing date 12.08.2019 Version number 2.0 Revision: 12.08.2019

Trade name: CHAINLUBE ADVENTURE SPRAY

	(Contd. of page
Transport/Additional information:	
ADR/RID/ADN	
Limited quantities (LQ)	1L
Excepted quantities (ÉQ)	Code: E0
,	Not permitted as Excepted Quantity
Transport category	2
Tunnel restriction code	D
·IMDG	
Limited quantities (LQ)	1L
Excepted quantities (ÉQ)	Code: E0
,	Not permitted as Excepted Quantity
UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

The classification of the mixture was carried out by calculation in accordance with the rules laid down in Annex I of Regulation (EC) No 1272/2008.

No special training instructions to ensure protection of human health and environment are required.

· Relevant phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

· Department issuing SDS: Abteilung Produktsicherheit

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

(Contd. on page 12)

Printing date 12.08.2019 Version number 2.0 Revision: 12.08.2019

Trade name: CHAINLUBE ADVENTURE SPRAY

(Contd. of page 11)

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1: Flammable gases - Category 1

Aerosol 1: Aerosols - Category 1

Press. Gas (Comp.): Gases under pressure – Compressed gas

Flam. Liq. 2: Flammable liquids – Category 2

Skin Irrit. 2: Skin corrosion/irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard — Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard — Category 3

* Data compared to the previous version altered.

Annex: Exposure scenario 1

· Short title of the exposure scenario

Industrial use of lubricants and greases in vehicles or machinery

· Sector of Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

- · Product category PC24 Lubricants, greases, release products
- · Process category

PROC1 Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.

PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions

PROC7 Industrial spraying

PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities

PROC9 Transfer of substance or mixture into small containers (dedicated filling line, including weighing)

PROC10 Roller application or brushing

PROC13 Treatment of articles by dipping and pouring

· Environmental release category

ERC4 Use of non-reactive processing aid at industrial site (no inclusion into or onto article)

- Description of the activities / processes covered in the Exposure Scenario See section 1 of the annex to the Safety Data Sheet.
- · Conditions of use
- · Duration and frequency 5 workdays/week.
- · Physical parameters
- Physical state Fluid
- · Concentration of the substance in the mixture The substance is main component.
- · Other operational conditions
- · Other operational conditions affecting environmental exposure

No special measures required.

- Other operational conditions affecting consumer exposure Not required.
- Other operational conditions affecting consumer exposure during the use of the product

Not applicable.

- Risk management measures
- · Worker protection
- · Organisational protective measures No special measures required.
- · Technical protective measures No special measures required.
- · Personal protective measures No special measures required.
- · Measures for consumer protection No special measures required.

(Contd. on page 13)

Printing date 12.08.2019 Version number 2.0 Revision: 12.08.2019

Trade name: CHAINLUBE ADVENTURE SPRAY

(Contd. of page 12)

- · Environmental protection measures
- · Air No special measures required.
- · Water No special measures required.
- · Disposal measures Ensure that waste is collected and contained.
- · Disposal procedures Dispose of product residues with household waste.
- · Waste type Partially emptied and uncleaned packaging
- · Exposure estimation
- · Consumer Not relevant for this Exposure Scenario.
- · Guidance for downstream users No further relevant information available.

Annex: Exposure scenario 2

· Short title of the exposure scenario

Professional use of lubricants and greases in open systems

· Sector of Use

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- Product category PC24 Lubricants, greases, release products
- · Process category

PROC1 Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.

PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions

PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

PROC10 Roller application or brushing

PROC11 Non industrial spraying

PROC13 Treatment of articles by dipping and pouring

Environmental release category

ERC8a Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor)

ERC8d Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)

- Description of the activities / processes covered in the Exposure Scenario See section 1 of the annex to the Safety Data Sheet.
- · Conditions of use
- · Duration and frequency 5 workdays/week.
- · Physical parameters
- · Physical state Fluid
- · Concentration of the substance in the mixture The substance is main component.
- · Other operational conditions
- · Other operational conditions affecting environmental exposure No special measures required.
- · Other operational conditions affecting consumer exposure Not required.
- Other operational conditions affecting consumer exposure during the use of the product

Not applicable.

- · Risk management measures
- · Worker protection
- · Organisational protective measures No special measures required.
- · Technical protective measures No special measures required.
- · Personal protective measures No special measures required.
- · Measures for consumer protection No special measures required.
- Environmental protection measures
- · Air No special measures required.

(Contd. on page 14)

Printing date 12.08.2019 Version number 2.0 Revision: 12.08.2019

Trade name: CHAINLUBE ADVENTURE SPRAY

(Contd. of page 13)

- · Water No special measures required.
- · Disposal measures Ensure that waste is collected and contained.
- · Disposal procedures Dispose of product residues with household waste.
- · Waste type Partially emptied and uncleaned packaging
- · Exposure estimation
- · Consumer Not relevant for this Exposure Scenario.
- · Guidance for downstream users No further relevant information available.

Annex: Exposure scenario 3

· Short title of the exposure scenario

Professional use of lubricants and greases in open systems

- · Sector of Use SU21 Consumer uses: Private households / general public / consumers
- Product category PC24 Lubricants, greases, release products
- · Environmental release category

ERC8a Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor)

ERC8d Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)

- Description of the activities / processes covered in the Exposure Scenario See section 1 of the annex to the Safety Data Sheet.
- · Conditions of use
- · Duration and frequency 5 workdays/week.
- · Physical parameters
- · Physical state Fluid
- · Concentration of the substance in the mixture The substance is main component.
- · Other operational conditions
- Other operational conditions affecting environmental exposure No special measures required.
- Other operational conditions affecting consumer exposure Not required.
- · Other operational conditions affecting consumer exposure during the use of the product

. Not applicable.

- Risk management measures
- Worker protection
- · Organisational protective measures No special measures required.
- · **Technical protective measures** No special measures required.
- · Personal protective measures No special measures required.
- · Measures for consumer protection No special measures required.
- · Environmental protection measures
- · Air No special measures required.
- · Water No special measures required.
- · Disposal measures Ensure that waste is collected and contained.
- Disposal procedures Dispose of product residues with household waste.
- · Waste type Partially emptied and uncleaned packaging
- · Exposure estimation
- · Consumer Not relevant for this Exposure Scenario.
- · Guidance for downstream users No further relevant information available.

GB