K&N Power Kleen

according to the Hazardous Products Regulation (February 11, 2015)

Date of issue: 07/29/2016 Version: 1.0

SECTION 1: Identification

1.1. Product identifier

Product form : Mixture

Product name : K & N Recharger cleaning Kit- Power Kleen (99-0606)

Product code : 99-0606 Power Kleen
Product group : Trade product

1.2. Recommended use and restrictions on use

Recommended uses and restrictions : Washing and cleaning products (including solvent based products)

1.3. Supplier

K&N Engineering, Inc.

P.O. Box 1329

92502-1329 Riverside, CA - USA T (800) 858-3333 - F (951) 826-4001

1.4. Emergency telephone number

Emergency number : Chemtrec (800) 424-9300 / +1 (703) 527-3887 (CCN 632715)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-CA)

Skin corrosion/irritation, Category 1C H314 Serious eye damage/eye irritation, Category 2A H319

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS-CA labelling

Hazard pictograms (GHS-CA)



GHS05

Signal word (GHS-CA) : Danger

Hazard statements (GHS-CA) : H314 - Causes severe skin burns and eye damage

H319 - Causes serious eye irritation

Precautionary statements (GHS-CA) : P260 - Do not breathe mist, fume, spray, vapours

P264 - Wash hands thoroughly after handling

P280 - Wear protective gloves/protective clothing/eye protection/face protection P301+P330+P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting

P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water

P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing

P310 - Immediately call a doctor

P321 - Specific treatment (see supplemental first aid instruction on this label)

P337+P313 - If eye irritation persists: Get medical advice/attention

P363 - Wash contaminated clothing before reuse

P405 - Store locked up

P501 - Dispose of contents/container to hazardous or special waste collection point, in

accordance with local, regional, national and/or international regulation

03/10/2016 EN (English) Page 1

K&N Power Kleen

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

: None.

Other hazards not contributing to the

classification

2.4. Unknown acute toxicity (GHS-CA)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%	Classification (GHS-CA)
Sodium metasilicate	Disodium metasilicate / Silicate, disodium / Silicic acid (H2SiO3), disodium salt / Sodium metasilicate, anhydrous / Silicic acid, disodium salt / Disodium metasilicate (Na2SiO3) / Disodium trioxosilicate / Silicic acid (H2SiO3), sodium salt (1:2) / SODIUM METASILICATE / Silicic acid, sodium salt (1:2) / Sodium silicate	(CAS No) 6834-92-0	2.065	Acute Tox. 4 (Oral), H302 Skin Corr. 1B, H314 STOT SE 3, H335

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Call a

physician immediately.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing. Call a physician immediately.

First-aid measures after ingestion : Rinse mouth. Do not induce vomiting. Call a physician immediately.

First-aid measures general : Call a physician immediately. Concerning personal protective equipment to use, see section 8.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/injuries after skin contact : Burns.

Symptoms/injuries after eye contact : Serious damage to eyes.

Symptoms/injuries after ingestion : Burns.

4.3. Immediate medical attention and special treatment, if necessary

Other medical advice or treatment : Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Unsuitable extinguishing media

Unsuitable extinguishing media : Do not use a heavy water stream.

5.3. Specific hazards arising from the hazardous product

Fire hazard : On combustion, forms: carbon oxides (CO and CO2).

5.4. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Exercise caution when fighting any chemical fire.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing

apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

No additional information available

6.2. Methods and materials for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Large quantities: Contain large spillage with sand or

earth. Small quantities of liquid spill: take up in non-combustible absorbent material and shovel into container for disposal. This material and its container must be disposed of in a safe way,

and as per local legislation.

Other information : Dispose of materials or solid residues at an authorized site.

03/10/2016 EN (English) SDS ID: 1459 2/12

K&N Power Kleen

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.3. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Avoid contact with skin and eyes. Do not breathe

fume, gas, mist, spray, vapours. Wear personal protective equipment.

Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product.

Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store locked up. Store in a well-ventilated place. Keep cool.

Incompatible products : Oxidizing agents and reducing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Solubility

Log Pow

Log Kow

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

8.3. Individual protection measures/Personal protective equipment

Hand protection : Chemically resistant protective gloves.

Eye protection : Chemical goggles or safety glasses. Eye protection, including both chemical splash goggles

and face shield, must be worn when possibility exists for eye contact due to spraying liquid or

airborne particles.

Skin and body protection : Long sleeved protective clothing.

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazard protection : Not available.

Environmental exposure controls : Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: LiquidAppearance: Powder.Colour: pink

Odour : characteristic
Odour threshold : No data available

pH : 12 - 13

· No data available pH solution Relative evaporation rate (butylacetate=1) : No data available Relative evaporation rate (ether=1) : No data available Melting point : Not applicable : <= 0 °C (32 °F) Freezing point Boiling point : >= 100 °C (212 °F) Flash point : No data available : No data available Auto-ignition temperature Decomposition temperature No data available Flammability (solid, gas) : Not applicable Vapour pressure : No data available Vapour pressure at 50 °C No data available Relative vapour density at 20 °C No data available Relative density : No data available Relative density of saturated gas/air mixture : No data available : No data available Density Relative gas density No data available

03/10/2016 EN (English) SDS ID: 1459 3/12

Water: Soluble

· No data available

: No data available

K&N Power Kleen

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Viscosity, kinematic : No data available Explosive properties : No data available : No data available Oxidising properties : No data available **Explosive limits**

Other information 9.2.

VOC content : <= 10 g/l

SECTION 10: Stability and reactivity

Reactivity : The product is non-reactive under normal conditions of use, storage and transport.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : No dangerous reactions known under normal conditions of use.

Conditions to avoid : None under recommended storage and handling conditions (see section 7).

: Reducing agents. Oxidizing agent. Incompatible materials

: Corrosive vapours. On combustion, forms: carbon oxides (CO and CO2). Hazardous decomposition products

SECTION 11: Toxicological information

Likely routes of exposure : Ingestion. Dermal. oral.

Information on toxicological effects

Acute toxicity (oral) Not classified Acute toxicity (dermal) : Not classified Acute toxicity (inhalation) : Not classified

Sodium	metasilicate	(6834-92-0)
Journalii	IIICLASIIICALC	10034-32-01

LD50 oral rat 1153 mg/kg

Skin corrosion/irritation : Causes severe skin burns and eye damage.

pH: 12 - 13

Serious eye damage/irritation : Causes serious eye damage.

pH: 12 - 13

Respiratory or skin sensitization : Not classified Germ cell mutagenicity : Not classified Carcinogenicity : Not classified : Not classified Reproductive toxicity Specific target organ toxicity (single exposure) : Not classified

Specific target organ toxicity (repeated

exposure)

: Not classified

Aspiration hazard : Not classified

SECTION 12: Ecological information

12.1. **Toxicity**

Ecology - general : Before neutralisation, the product may represent a danger to aquatic organisms.

Sodium metasilicate (6834-92-0)	
LC50 fish 1	210 mg/l (Exposure time: 96 h - Species: Brachydanio rerio [semi-static])
LC50 fish 2	210 mg/l (Exposure time: 96 h - Species: Brachydanio rerio)

Persistence and degradability

No additional information available

Bioaccumulative potential

No additional information available

Mobility in soil

No additional information available

03/10/2016 SDS ID: 1459 4/12 EN (English)

K&N Power Kleen

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.5. Other adverse effects

Other adverse effects : None known.

GWPmix comment : No known effects from this product.

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Sewage disposal recommendations : Do not allow into drains or water courses.

Waste disposal recommendations : Avoid release to the environment. Dispose in a safe manner in accordance with local/national

regulations.

SECTION 14: Transport information

14.1. Basic shipping description

In accordance with TDG

Transportation of Dangerous Goods

Not regulated for transport

14.2. Transport information/DOT

No additional information available

14.3. Air and sea transport

IMDG

Not regulated for transport

ΙΔΤΔ

Class (IATA) : Not regulated for transport

SECTION 15: Regulatory information

15.1. National regulations

K & N Power Kleen (99-0606)

Listed on the Canadian DSL (Domestic Substances List)

Sodium metasilicate (6834-92-0)

Listed on the Canadian DSL (Domestic Substances List)

15.2. International regulations

Sodium metasilicate (6834-92-0)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on the Korean ECL (Existing Chemicals List)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Listed on CICR (Turkish Inventory and Control of Chemicals)

SECTION 16: Other information

Date of issue : 29/07/2016

Full text of H-statements:

At 0111-statements.	
H302	Harmful if swallowed
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H318	Causes serious eye damage
H335	May cause respiratory irritation
H400	Very toxic to aquatic life

SDS Canada (GHS)

03/10/2016 EN (English) SDS ID: 1459 5/12

K&N Power Kleen

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product

03/10/2016 EN (English) SDS ID: 1459 6/12

K&N Air Filter Squeeze Oil

according to the Hazardous Products Regulation (February 11, 2015)

Date of issue: 07/29/2016 Version: 1.0

SECTION 1: Identification

1.1. Product identifier

Product form : Mixture

Product name : K&N Recharger cleaning Kit- Air Filter Squeeze Oil (99-0503)

Product code : 99-5050 Recharger Cleaning Kit

Product group : Trade product

1.2. Recommended use and restrictions on use

Recommended uses and restrictions : Lubricant
Recommended use : Industrial use

1.3. Supplier

K&N Engineering, Inc. P.O. Box 1329

92502-1329 Riverside, CA - USA T (800) 858-3333 - F (951) 826-4001

1.4. Emergency telephone number

Emergency number : Chemtrec (800) 424-9300 / +1 (703) 527-3887 (CCN 632715)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-CA)

Carcinogenicity, Category 1B H350 Aspiration hazard, Category 1 H304 Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS-CA labelling

Hazard pictograms (GHS-CA)



Donger

Signal word (GHS-CA) : Danger

Hazard statements (GHS-CA) : H304 - May be fatal if swallowed and enters airways

H350 - May cause cancer

Precautionary statements (GHS-CA) : P201 - Obtain special instructions before use

P202 - Do not handle until all safety precautions have been read and understood P280 - Wear protective gloves/protective clothing/eye protection/face protection P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor

P308+P313 - IF exposed or concerned: Get medical advice/attention

P331 - Do NOT induce vomiting

P405 - Store locked up

P501 - Dispose of contents/container to hazardous or special waste collection point, in

accordance with local, regional, national and/or international regulation

2.3. Other hazards

Other hazards not contributing to the : None.

classification

2.4. Unknown acute toxicity (GHS-CA)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

03/10/2016 EN (English) Page 1

K&N Air Filter Squeeze Oil

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%	Classification (GHS-CA)
Distillates, petroleum, hydrotreated heavy paraffinic (K&N)	Petroleum distillates, hydrotreated heavy paraffinic / Distillates (petroleum), hydrotreated heavy paraffinic / Distillates (petroleum), hydrotreated heavy paraffinic - base oil - unspecified / Distillates (petroleum) hydrotreated heavy paraffinic / Heavy base oils / Paraffin oil / Distillates, petroleum, hydrotreated heavy paraffinic (A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20-50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.)	(CAS No) 64742-54-7	60 - 100	Carc. 1B, H350

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : Wash skin with plenty of water.

First-aid measures after eye contact : Rinse eyes with water as a precaution.

First-aid measures after ingestion : Do not induce vomiting. Call a physician immediately.

First-aid measures general : Call a physician immediately. If you feel unwell, seek medical advice (show the label where

possible). Concerning personal protective equipment to use, see section 8.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/injuries : Not expected to present a significant hazard under anticipated conditions of normal use.

Symptoms/injuries after ingestion : Risk of lung oedema. Chronic symptoms : May cause cancer.

4.3. Immediate medical attention and special treatment, if necessary

Other medical advice or treatment : Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Unsuitable extinguishing media

Unsuitable extinguishing media : None known.

5.3. Specific hazards arising from the hazardous product

Fire hazard : On combustion, forms: carbon oxides (CO and CO2).

5.4. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing

apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Avoid contact with skin and eyes.

6.2. Methods and materials for containment and cleaning up

For containment : Containment: Contain any spills with dikes or absorbents to prevent migration and entry into

sewers or public waters.

Methods for cleaning up : Notify authorities if product enters sewers or public waters. In case of large spillages: Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Shovel or

spills with inert solids, such as clay or diatomaceous earth as soon as possible. Shovel or sweep up and put in a closed container for disposal. Small quantities of liquid spill: take up in non-combustible absorbent material and shovel into container for disposal. Stop leak if safe to

Other information : Dispose of materials or solid residues at an authorized site.

03/10/2016 EN (English) SDS ID: 1459 8/12

K&N Air Filter Squeeze Oil

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.3. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Do not handle until all safety precautions have

been read and understood. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Provide local exhaust or general room ventilation. Wear personal protective equipment. Take all necessary technical measures to avoid or

minimize the release of the product on the workplace.

Hygiene measures : Separate working clothes from town clothes. Launder separately. Do not eat, drink or smoke

when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store locked up. Store in a well-ventilated place. Keep cool. Keep away from open flames, hot

surfaces and sources of ignition.

Incompatible products : Oxidizing agent.

Maximum storage period : 60 months

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

8.3. Individual protection measures/Personal protective equipment

Hand protection : Protective gloves. Eye protection : Safety glasses.

Skin and body protection : Wear suitable protective clothing.

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment.

: No data available

Thermal hazard protection : Not available.

Environmental exposure controls : Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Appearance : Oily. Liquid.
Colour : red

Odour : characteristic petroleum Odour

Odour threshold No data available pН : No data available pH solution : No data available Relative evaporation rate (butylacetate=1) : No data available Relative evaporation rate (ether=1) : No data available Melting point : Not applicable Freezing point : No data available : > 260 °C (500 °F) Boiling point Flash point : > 232 °C (450 °F) Auto-ignition temperature : No data available Decomposition temperature : No data available Flammability (solid, gas) : Not applicable Vapour pressure : No data available Vapour pressure at 50 °C : No data available

Relative density : 0.864

Relative vapour density at 20 °C

Relative density of saturated gas/air mixture : No data available

Density : No data available

Relative gas density : No data available

03/10/2016 EN (English) SDS ID: 1459 9/12

K&N Air Filter Squeeze Oil

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Solubility : Negligible.

Log Pow : No data available

Log Kow : No data available

Viscosity, kinematic : No data available

Explosive properties : No data available

Oxidising properties : No data available

Explosive limits : No data available

9.2. Other information

Minimum ignition energy : ≈

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity : The product is non-reactive under normal conditions of use, storage and transport.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : No dangerous reactions known under normal conditions of use.

Conditions to avoid : None under recommended storage and handling conditions (see section 7).

Incompatible materials : Oxidizing agent.

Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be

produced. On combustion, forms: carbon oxides (CO and CO2).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Distillates, petroleum, hydrotreated heavy paraffinic (K&N) (64742-54-7)	
LD50 oral rat	> 2000 mg/kg
LD50 dermal rabbit	> 2 g/kg
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified

Reproductive toxicity : Not classified Specific target organ toxicity (single exposure) : Not classified Specific target organ toxicity (repeated : Not classified

exposure)

Carcinogenicity

: May cause cancer.

Aspiration hazard : May be fatal if swallowed and enters airways.

K&N Air Filter Oil	
Viscosity, kinematic (calculated value) (40 °C)	>= 7.5 mm²/s @ 100 °C (212 °F)

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

Distillates, petroleum, hydrotreated heavy paraffinic (K&N) (64742-54-7)	
LC50 fish 1	> 5000 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
EC50 Daphnia 1	> 1000 mg/l (Exposure time: 48 h - Species: Daphnia magna)

03/10/2016 EN (English) SDS ID: 1459 10/12

K&N Air Filter Squeeze Oil

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.2. Persistence and degradability

K&N Air Filter Oil		
	Persistence and degradability	Not established.

12.3. Bioaccumulative potential

K&N Air Filter Oil		
	Bioaccumulative potential	Not established.

12.4. Mobility in soil

K&N Air Filter Oil	
Ecology - soil	Not established.

12.5. Other adverse effects

Effect on the global warming : Not established.

GWPmix comment : No known effects from this product.

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Sewage disposal recommendations : Do not allow into drains or water courses.

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

SECTION 14: Transport information

14.1. Basic shipping description

In accordance with TDG

TDG

Not regulated for transport

14.2. Transport information/DOT

DOT

Not regulated for transport

14.3. Air and sea transport

IMDG

Class (IMDG) : Not regulated for transport

IATA

Class (IATA) : Not regulated for transport

SECTION 15: Regulatory information

15.1. National regulations

Distillates, petroleum, hydrotreated heavy paraffinic (K&N) (64742-54-7)

Listed on the Canadian DSL (Domestic Substances List)

1-Decene, homopolymer, hydrogenated (68037-01-4)

Listed on the Canadian DSL (Domestic Substances List)

15.2. International regulations

Distillates, petroleum, hydrotreated heavy paraffinic (K&N) (64742-54-7)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Listed on the Korean ECL (Existing Chemicals List)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Listed on CICR (Turkish Inventory and Control of Chemicals)

03/10/2016 EN (English) SDS ID: 1459 11/12

K&N Air Filter Squeeze Oil

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

1-Decene, homopolymer, hydrogenated (68037-01-4)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on the Korean ECL (Existing Chemicals List)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on CICR (Turkish Inventory and Control of Chemicals)

SECTION 16: Other information

Date of issue : 29/07/2016

Full text of H-statements:

H304	May be fatal if swallowed and enters airways
H350	May cause cancer

SDS Canada (GHS)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product

03/10/2016 EN (English) SDS ID: 1459 12/12