

according to 1907/2006/EC, Article 31

Printing date 03.02.2014

Version number 1

Revision: 03.02.2014

1 Identification of the substance/mixture and of the company/ undertaking

· Product identifier

- · Trade name: LEGEND 4T SAE 20W/50
- **Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available.
- Application of the substance / the mixture Engine oil Only for proper handling.
- Details of the supplier of the safety data sheet • Manufacturer/Supplier:

BUCHER AG LANGENTHAL MOTOREX–Schmiertechnik Bern–Zürich–Strasse 31 CH–4901 Langenthal Telefon +41 (0)62 919 75 75

· Only representative in EU:

MOTOREX Deutschland AG, Bismarckstrasse 28, D-69198 Schriesheim

 Further information obtainable from: <u>msds@motorex.com</u>
 Emergency telephone number: Toxicological Information Centre, CH-8028 Zurich, <u>info@toxi.ch</u>, T. +41 (0) 44 251 51 51

2 Hazards identification

- · Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008 The product is not classified according to the CLP regulation.
- Classification according to Directive 67/548/EEC or Directive 1999/45/EC Not applicable.
- Information concerning particular hazards for human and environment: The product does not have to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.
- *Classification system:* The classification is according to the latest editions of the EU-lists, and extended by company and literature data.
- · Label elements
- · Labelling according to Regulation (EC) No 1272/2008 Void
- · Hazard pictograms Void
- · Signal word Void
- · Hazard statements Void
- · Additional information:

Contains Calcium alkaryl sulfonate,. May produce an allergic reaction. Safety data sheet available on request.

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

(Contd. on page 2)

according to 1907/2006/EC, Article 31 Version number 1

Revision: 03.02.2014

Trade name: LEGEND 4T SAE 20W/50

Printing date 03.02.2014

(Contd. of page 1)

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous compo	nents:	
CAS: 64742-54-7 EINECS: 265-157-1	Distillates (petroleum), hydrotreated heavy paraffinic	10-25%
Polymer	Polyolefin polyamine succinimide, polyol R53 Aquatic Chronic 4, H413	1-2.5%
CAS: 68649-42-3 EINECS: 272-028-3	🗙 Xi R41; 🏪 N R51/53	0.25-1%
Polymer	 Eye Dam. 1, H318; Aquatic Chronic 2, H411 Branched alkyl phenol and calcium branched alkyl phenol Xn R62; Xi R38; N R50/53 Repr. Cat. 3 	0.1-0.25%
	 Repr. 2, H361; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Irrit. 2, H315 	

· Additional information: For the wording of the listed risk phrases refer to section 16.

4 First aid measures

- · Description of first aid measures
- · General information: No special measures required.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Remove residues with soap and water. Remove contaminated clothing immediately.
- · After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: Do not induce vomitting. Do not take in resorption stimulating agents. Consult a physician who will decide on need and method of emptying the stomach.
- · Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Firefighting measures

- Extinguishing media
- Suitable extinguishing agents:
- Use fire extinguishing methods suitable to surrounding conditions.
- Special hazards arising from the substance or mixture
- In case of fire carbon, sulphur and phosphorus oxides can be formed.
- · Advice for firefighters
- Protective equipment: No special measures required.

(Contd. on page 3)

according to 1907/2006/EC, Article 31 Version number 1

Revision: 03.02.2014

Trade name: LEGEND 4T SAE 20W/50

Printing date 03.02.2014

(Contd. of page 2)

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Not required.
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- *Methods and material for containment and cleaning up:* Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders,
- sawdust). • **Reference to other sections** No dangerous substances are released. See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Used oils (motor oils, gear oils, industrial oils) contain components causing skin cancer. Therefore, avoid skin contact by wearing protecting gloves. Carefully clean soiled parts of the skin with soap.

- No special measures required.
- · Information about fire and explosion protection: Do not heat above flash point.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Store containers closed and protect against rain, dust, heat and other atmospheric influences.

- · Storage class: 10
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

- · Control parameters
- Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:
- The usual precautionary measures are to be adhered to when handling chemicals.
- · Respiratory protection: Not required.
- · Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Contd. on page 4)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 03.02.2014

Version number 1

Revision: 03.02.2014

Trade name: LEGEND 4T SAE 20W/50

· Material of gloves

(Contd. of page 3)

GB

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Goggles recommended during refilling

Information on basic physical and	chemical properties
General Information	
Appearance: Form:	Fluid
Colour:	Brown
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	Undetermined.
Flash point:	> 200 °C
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	260 °C (DIN 51794)
Decomposition temperature:	Not determined.
Self-igniting:	Product is not selfigniting.
Danger of explosion:	Product does not present an explosion hazard.
Explosion limits:	
Lower:	0.9 Vol %
Upper:	7.0 Vol %
Vapour pressure:	< 0.1 hPa (20 °C)
Density at 20 °C:	0.885 g/cm³ (ASTM D 4052)
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wat	ter): Not determined.
Viscosity:	169 mm2/s @ 40 °C
Dynamic:	Not determined.
Kinematic: VOC (EC)	169 mm²/s @ 40 °C (DIN 51562-1) 0.00 %

according to 1907/2006/EC, Article 31 Version number 1

Revision: 03.02.2014

Trade name: LEGEND 4T SAE 20W/50

(Contd. of page 4)

Other information

Printing date 03.02.2014

No further relevant information available.

10 Stability and reactivity

- · Reactivity
- · Chemical stability
- · Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product is not subject to classification according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version. When used and handled according to specifications, the product does not have any harmful effects to our experience and the information provided to us.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-classification according VwVwS, 17.05.1999): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation Smaller quantities can be disposed of with household waste.

(Contd. on page 6)

according to 1907/2006/EC, Article 31

Revision: 03.02.2014

Trade name: LEGEND 4T SAE 20W/50

· European waste catalogue

13 02 05* mineral-based non-chlorinated engine, gear and lubricating oils

· Uncleaned packaging:

· Recommendation: Disposal must be made according to official regulations.

4 Transport information		
· UN-Number · ADR, ADN, IMDG, IATA	Void	
 UN proper shipping name ADR, ADN, IMDG, IATA 	Void	
· Transport hazard class(es)		
· ADR, ADN, IMDG, IATA · Class	Void	
· Packing group · ADR, IMDG, IATA	Void	
 Environmental hazards: Marine pollutant: 	No	
· Special precautions for user	Not applicable.	
 Transport in bulk according to Annex MARPOL73/78 and the IBC Code 	ll of Not applicable.	
· UN "Model Regulation":	-	

15 Regulatory information

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H361 Suspected of damaging fertility or the unborn child.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.
- H413 May cause long lasting harmful effects to aquatic life.
- R38 Irritating to skin.
- R41 Risk of serious damage to eyes.
- R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

(Contd. on page 7) GB

Version number 1

(Contd. of page 5)

GB

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 03.02.2014

Version number 1

Revision: 03.02.2014

Trade name: LEGEND 4T SAE 20W/50

(Contd. of page 6) R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R53 May cause long-term adverse effects in the aquatic environment.

R62 Possible risk of impaired fertility.

· Department issuing MSDS: Abteilung Produktsicherheit