

Printing date 01.02.2016

### Version number 1

Revision: 01.02.2016

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

- · Trade name: RACING BIO LIQUID POWER AIR FILTER OIL
- **1.2 Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available.
- Application of the substance / the mixture Air filter oil Only for proper handling.
- 1.3 Details of the supplier of the safety data sheet
   Manufacturer/Supplier:

BUCHER\_AG\_LANGENTHAL MOTOREX–Schmiertechnik Bern–Zürich–Strasse\_31\_\_ CH–4901\_Langenthal\_\_ Telefon\_+41\_(0)62\_919\_75\_75

 Further information obtainable from: <u>msds@motorex.com</u>
 1.4 Emergency telephone number: Toxicological Information Centre, CH-8028 Zurich, <u>info@toxi.ch</u>, T. +41 (0) 44 251 51 51

### **SECTION 2: Hazards identification**

2.1 Classification of the substance or mixture
 Classification according to Regulation (EC) No 1272/2008

GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

GHS08 health hazard

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

GHS07 Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

according to (EU) 2015/830

Printing date 01.02.2016

Version number 1

Revision: 01.02.2016

	(Contd. of pag
<ul> <li>Hazard pictog</li> </ul>	grams
GHS02 GHS	S07 GHS08 GHS09
· Signal word [	Danger
· Hazard-deteri	mining components of labelling:
	C6-C7, n-alkanes, iso-alkanes, cyclenes, <5% n-hexane
· Hazard staten	
H225 Highly fla	lammable liquid and vapour.
H315 Causes	
H336 May cau	use drowsiness or dizziness.
	fatal if swallowed and enters airways.
	aquatic life with long lasting effects.
· Precautionary	
P210	Keep away from heat, hot surfaces, sparks, open flames and or ignition sources. No smoking.
P241	Use explosion-proof electrical/ventilating/lighting/equipment.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
	Wear protective gloves/protective clothing/eye protection/face protect
P280	Ground/bond container and receiving equipment.
P280 P240	
P240 P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P240 P301+P310	P353 IF ON SKIN (or hair): Take off immediately all contaminated cloth
P240 P301+P310 P303+P361+P	
P240 P301+P310	P353 IF ON SKIN (or hair): Take off immediately all contaminated cloth
P240 P301+P310 P303+P361+P	P353 IF ON SKIN (or hair): Take off immediately all contaminated cloth Rinse skin with water/shower.

· **PBT:** Not applicable. · vPvB: Not applicable.

### SECTION 3: Composition/information on ingredients

### · 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:			
EC number: 921-024-6 Reg.nr.: 01-2119475514-35-xxxx	Hydrocarbons C6-C7, n-alkanes, iso-alkanes, cvclenes, <5% n-hexane	50-70%	
	<ul> <li>Flam. Liq. 2, H225;</li> <li>Asp. Tox. 1, H304;</li> <li>Aquatic Chronic 2, H411;</li> <li>Skin Irrit. 2, H315; STOT SE 3, H336</li> </ul>		
• Additional information: For the wording of the listed hazard phrases refer to section 16			

### SECTION 4: First aid measures

### · 4.1 Description of first aid measures

· After inhalation:

In case of unconsciousness place patient stably in side position for transportation.

(Contd. on page 3) GB

Printing date 01.02.2016

Version number 1

Revision: 01.02.2016

### Trade name: RACING BIO LIQUID POWER AIR FILTER OIL

(Contd. of page 2)

- After skin contact: Remove contaminated clothing immediately. Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. Consult a physician if irritation develops.
- After swallowing: Do not induce vomitting. Do not take in resorption stimulating agents.
   Consult a physician who will decide on need and method of emptying the stomach.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

### **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.
- Additional information Use water spray to cool fire exposed containers and fire affected zone until fire is out and danger of reignition has passed.

### SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions: Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
- **6.3** *Methods and material for containment and cleaning up:* Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.
  - Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

- 6.4 Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.

(Contd. on page 4)

according to (EU) 2015/830

Printing date 01.02.2016

Version number 1

Revision: 01.02.2016

### Trade name: RACING BIO LIQUID POWER AIR FILTER OIL

(Contd. of page 3)

- 7.2 Conditions for safe storage, including any incompatibilities
   Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

- Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

### SECTION 8: Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

- · 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace: The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- Additional information: The lists valid during the making were used as basis.

#### · 8.2 Exposure controls

- · Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the skin. Avoid contact with the eyes and skin.
- · Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

### Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

### · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

GB

Printing date 01.02.2016

Version number 1

Revision: 01.02.2016

### Trade name: RACING BIO LIQUID POWER AIR FILTER OIL

(Contd. of page 4)

· Eye protection:

Tightly sealed goggles

## SECTION 9: Physical and chemical properties

• 9.1 Information on basic physical a	nd chemical properties
<ul> <li>General Information</li> <li>Appearance: Form: Colour:</li> <li>Odour:</li> <li>Odour:</li> <li>Odour threshold:</li> </ul>	Fluid Dark green Solvent-like Not determined.
· pH-value:	Not determined.
<ul> <li>Change in condition Melting point/Melting range: Boiling point/Boiling range:</li> </ul>	Undetermined. 65 °C (DIN EN ISO 3405)
· Flash point:	< -20 °C
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	250 °C (DIN 51794)
· Decomposition temperature:	Not determined.
· Self-igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation o explosive air/vapour mixtures are possible.
<ul> <li>Explosion limits: Lower: Upper:</li> </ul>	1.0 Vol % 7.3 Vol %
<ul> <li>Vapour pressure at 20 °C:</li> </ul>	1.9 hPa
· Density at 20 °C:	0.781 g/cm³ (ASTM D 4052)
<ul> <li>Density at 15 °C:</li> <li>Relative density</li> <li>Vapour density</li> <li>Evaporation rate</li> </ul>	0.785 g/cm <sup>3</sup> Not determined. Not determined. Not determined.
<ul> <li>Solubility in / Miscibility with water:</li> </ul>	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/wat	er): Not determined.
<ul> <li>Viscosity:</li> <li>Dynamic:</li> <li>Kinematic:</li> <li>VOC (EC)</li> <li>9.2 Other information</li> </ul>	Not determined. 7.1 mm²/s @ 40 °C (DIN 51562-1) 59.98 % No further relevant information available.

(Contd. on page 6)

according to (EU) 2015/830

Printing date 01.02.2016

Version number 1

Revision: 01.02.2016

### Trade name: RACING BIO LIQUID POWER AIR FILTER OIL

(Contd. of page 5)

### SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- **Thermal decomposition / conditions to be avoided:** Can be distilled without decomposing at normal pressure.

10.3 Possibility of hazardous reactions No dangerous reactions known.

- 10.4 Conditions to avoid With strong oxidisers.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.
- · Additional information: The product is highly flammable.

### **SECTION 11: Toxicological information**

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · Primary irritant effect:
- · Skin corrosion/irritation
- Causes skin irritation.
- · Serious eye damage/irritation
- Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation
- Based on available data, the classification criteria are not met.
- $\cdot$  CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure
- May cause drowsiness or dizziness.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard
- May be fatal if swallowed and enters airways.

### SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability
- Biodegradability according to OECD 301 B: >60 % in 28 days
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-classification according VwVwS, 17.05.1999): hazardous for water

- Do not allow product to reach ground water, water course or sewage system.
- Danger to drinking water if even small quantities leak into the ground.
- Also poisonous for fish and plankton in water bodies.
- Toxic for aquatic organisms
- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.

(Contd. on page 7)

according to (EU) 2015/830

Printing date 01.02.2016

Version number 1

Revision: 01.02.2016

(Contd. of page 6)

### Trade name: RACING BIO LIQUID POWER AIR FILTER OIL

· vPvB: Not applicable.

· 12.6 Other adverse effects No further relevant information available.

### **SECTION 13: Disposal considerations**

### · 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

12 01 19\* readily biodegradable machining oil

### · Uncleaned packaging:

· Recommendation:

Disposal must be made according to official regulations.

Discharged containers can contain flammable or explosive vapours.

14.1 UN-Number ADR,ADN, IMDG, IATA	UN3295
14.2 UN proper shipping name ADR/ADN	3295 HYDROCARBONS, LIQUID, N.O.S
IMDG	ENVIRONMENTALLY HAZARDOUS HYDROCARBONS, LIQUID, N.O.S (Naphtha (petroleum), hydrotreated light MARINE POLLUTANT
ΙΑΤΑ	Hydrocarbons, liquid, n.o.s.
14.3 Transport hazard class(es)	
ADR/ADN	
Class Label	3 (F1) Flammable liquids. 3
IMDG	
Class	3 Flammable liquids.
Label	3
ΙΑΤΑ	

according to (EU) 2015/830

Printing date 01.02.2016

Version number 1

Revision: 01.02.2016

### Trade name: RACING BIO LIQUID POWER AIR FILTER OIL

	(Contd. of page
Label	3
14.4 Packing group ADR,ADN, IMDG, IATA	11
14.5 Environmental hazards: Marine pollutant: Special marking (ADR/ADN):	Symbol (fish and tree) Symbol (fish and tree)
14.6 Special precautions for user Danger code (Kemler): EMS Number: Stowage Category	Warning: Flammable liquids. 33 F-E,S-D B
<i>14.7 Transport in bulk according to A</i> <i>II of Marpol and the IBC Code</i>	nnex Not applicable.
Transport/Additional information:	
ADR/ADN Limited quantities (LQ) Excepted quantities (EQ) Transport category Tunnel restriction code	1L Code: E2 Maximum net quantity per inner packaging 30 ml Maximum net quantity per outer packaging 500 ml 2 D/E
<i>IMDG Limited quantities (LQ) Excepted quantities (EQ)</i>	1L Code: E2 Maximum net quantity per inner packagin 30 ml Maximum net quantity per outer packagin 500 ml
UN "Model Regulation":	UN 3295 HYDROCARBONS, LIQUI N.O.S., 3, II, ENVIRONMENTALL HAZARDOUS

### SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category
- E2 Hazardous to the Aquatic Environment
- P5c FLAMMABLE LIQUIDS
- $\cdot$  Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- $\cdot$  Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

### · National chemical directories

Components listed or exempted from listing: TSCA (USA) DSL/NDSL (CDN) ENCS/METI (J)

(Contd. on page 9)

GB

Printing date 01.02.2016

Version number 1

Revision: 01.02.2016

### Trade name: RACING BIO LIQUID POWER AIR FILTER OIL

(Contd. of page 8)

GB

AICS (Aus) IECSC (CN) EINECS/ELINCS/NLP (EU) ECL/KECI (KOR)

 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H225 Highly flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

· Department issuing MSDS: Abteilung Produktsicherheit

### · Abbreviations and acronyms:

Flam. Liq. 2: Flammable liquids, Hazard Category 2 Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

Asp. Tox. 1: Aspiration hazard, Hazard Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2