

Printing date 22.12.2015

Version number 1

Revision: 22.12.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

- · Trade name: SILICONE SPRAY
- **1.2 Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available.
- Application of the substance / the mixture Lubrication, anticorrosive Only for proper handling.
- 1.3 Details of the supplier of the safety data sheet Manufacturer/Supplier:

BUCHER_AG_LANGENTHAL MOTOREX–Schmiertechnik Bern–Zürich–Strasse_31__ CH–4901_Langenthal__ Telefon_+41_(0)62_919_75_75

· Only representative in EU:

MOTOREX Deutschland AG, Bismarckstrasse 28, D-69198 Schriesheim

 Further information obtainable from: <u>msds@motorex.com</u>
 1.4 Emergency telephone number: Toxicological Information Centre, CH-8028 Zurich, <u>info@toxi.ch</u>, T. +41 (0) 44 251 51 51

| • 2.1 Classification • Classification ac | n of the subs cording to R | | |
|---|-------------------------------|--|--------------------|
| Aerosol 1 | H222-H229 | Extremely flammable aerosol. Pressurised burst if heated. | container: May |
| <u> </u> | environment | | |
| Aquatic Chronic 2 | H411 | Toxic to aquatic life with long lasting effects. | |
| GHS07 | | | |
| STOT SE 3 | H336 | May cause drowsiness or dizziness. | |
| | ing to Regul | ation (EC) No 1272/2008 belled according to the CLP regulation. | (Contd. on page 2) |

Version number 1

Revision: 22.12.2015

Trade name: SILICONE SPRAY

Printing date 22.12.2015

| Hazard pi | ictograms (Contd. of page |
|-----------|---|
| | |
| <u>5</u> | |
| GHS02 | GHS07 GHS09 |
| Signal wo | ord Danger |
| Hazard-de | etermining components of labelling: |
| | oons, C7-C9, n-alkanes, isoalkanes, cyclics |
| Hazard st | |
| H222-H22 | 9 Extremely flammable aerosol. Pressurised container: May burst if heated. |
| H336 | May cause drowsiness or dizziness. |
| H411 | Toxic to aquatic life with long lasting effects. |
| Precautio | nary statements |
| P101 | If medical advice is needed, have product container or label at hand. |
| P102 | Keep out of reach of children. |
| P103 | Read label before use. |
| P210 | Keep away from heat, hot surfaces, sparks, open flames and other igniti sources. No smoking. |
| P251 | Do not pierce or burn, even after use. |
| P211 | Do not spray on an open flame or other ignition source. |
| P261 | Avoid breathing dust/fume/gas/mist/vapours/spray. |
| P304+P34 | 40 IF INHALED: Remove person to fresh air and keep comfortable for breathing |
| P312 | Call a POISON CENTER/doctor if you feel unwell. |
| P405 | Store locked up. |
| P410+P41 | 12 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °I |
| P403+P23 | 33 Store in a well-ventilated place. Keep container tightly closed. |
| P501 | Dispose of contents/container in accordance with local/regional/nation international regulations. |
| | |
| 2.3 Other | hazards |

PBT: Not applicable.
 vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· **Description:** Mixture of substances listed below with nonhazardous additions.

| CAS: 106-97-8 | butane | 25-50% |
|--|--|--------|
| EINECS: 203-448-7 Reg.nr.: 01-2119474691-32 | 🚸 Flam. Gas 1, H220; Press. Gas C, H280 | |
| Reg.nr.: 01-2119473851-33-xxxx | | 25-50% |
| | ♦ Flam. Liq. 2, H225; ♦ Asp. Tox. 1, H304; ♦ Aquatic Chronic 2, H411; ♦ STOT SE 3, H336 | |
| CAS: 74-98-6 | propane | 10-25% |
| EINECS: 200-827-9 Reg.nr.: 01-2119486944-21 | Flam. Gas 1, H220; Press. Gas C, H280 | |

Printing date 22.12.2015

Version number 1

Revision: 22.12.2015

Trade name: SILICONE SPRAY

| | (Co | ontd. of page 2) |
|---------------------------|--|------------------|
| CAS: 75-28-5 | isobutane | 1-2.5% |
| EINECS: 200-857-2 | 🚸 Flam. Gas 1, H220; Flam. Liq. 1, H224; | |
| Reg.nr.: 01-2119485395-27 | Press. Gas C, H280 | |
| | | |

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture
- No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- · 6.2 Environmental precautions: Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up: Ensure adequate ventilation.
- Do not flush with water or aqueous cleansing agents
- · 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling Open and handle receptacle with care.

- Information about fire and explosion protection: Keep ignition sources away - Do not smoke.
- Protect against electrostatic charges.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

(Contd. on page 4)

GB

according to (EU) 2015/830 Version number 1

Revision: 22.12.2015

(Contd. of page 3)

Trade name: SILICONE SPRAY

Printing date 22.12.2015

Do not spray onto a naked flame or any incandescent material.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles:
 Store in a cool location.
 Observe official regulations on storing packagings with pressurised containers.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed. Do not seal receptacle gas tight.

Store in cool, dry conditions in well sealed receptacles.

- Protect from heat and direct sunlight.
- Storage class: 2 B
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

106-97-8 butane

WEL Short-term value: 1810 mg/m³, 750 ppm

Long-term value: 1450 mg/m³, 600 ppm

Carc (if more than 0.1% of buta-1.3-diene)

· Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

- · Personal protective equipment:
- · General protective and hygienic measures:

Wash hands before breaks and at the end of work.

- · Respiratory protection: Not required.
- · Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

Printing date 22.12.2015

Version number 1

Revision: 22.12.2015

(Contd. of page 4)

Trade name: SILICONE SPRAY

· Eye protection:

Tightly sealed goggles

SECTION 9: Physical and chemical properties

| 9.1 Information on basic physical a General Information | and chemical properties |
|---|--|
| Appearance: Form: Colour: Odour: Odour threshold: | Liquefied gas Colourless Solvent-like Not determined. |
| · pH-value: | Not determined. |
| Change in condition Melting point/Melting range: Boiling point/Boiling range: | Undetermined. Not applicable, as aerosol. |
| Flash point: | < -40 °C |
| Flammability (solid, gaseous): | Not applicable. |
| Ignition temperature: | 470 °C (DIN 51794) |
| Decomposition temperature: | Not determined. |
| Self-igniting: | Product is not selfigniting. |
| Danger of explosion: | Product is not explosive. However, formation c explosive air/vapour mixtures are possible. |
| Explosion limits: Lower: Upper: | 1.7 Vol % 10.9 Vol % |
| Vapour pressure at 20 °C: | 8300 hPa |
| Density at 20 °C: Relative density Vapour density Evaporation rate | 0.65 g/cm ³ (ASTM D 4052) Not determined. Not determined. Not applicable. |
| · Solubility in / Miscibility with water: | Not miscible or difficult to mix. |
| · Partition coefficient (n-octanol/wat | ter): Not determined. |
| Viscosity: Dynamic: Kinematic: VOC (EC) 9.2 Other information | Not determined. < 1 mm²/s @40 °C (DIN 51562-1) 87.10 % No further relevant information available. |

(Contd. on page 6)

GB

according to (EU) 2015/830

Printing date 22.12.2015

Version number 1

Revision: 22.12.2015

Trade name: SILICONE SPRAY

(Contd. of page 5)

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation
- Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation
- Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure
- May cause drowsiness or dizziness.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-classification according VwVwS, 17.05.1999): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

(Contd. on page 7)

GF

according to (EU) 2015/830

Printing date 22.12.2015

Version number 1

Revision: 22.12.2015

Trade name: SILICONE SPRAY

(Contd. of page 6)

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

16 05 04^{*} gases in pressure containers (including halons) containing hazardous substances

· Uncleaned packaging:

· Recommendation:

Disposal must be made according to official regulations. Discharged containers can contain flammable or explosive vapours.

| 14.1 UN-Number ADR,ADN, IMDG, IATA | UN1950 |
|---|---|
| 14.2 UN proper shipping name ADR/ADN | 1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS |
| IMDG | AEROSOLS (Naphtha (petroleum) hydrotreated light, isopentane), MARINE POLLUTANT |
| ΙΑΤΑ | Aerosols, flammable |
| 14.3 Transport hazard class(es) | |
| ADR/ADN | |
| | |
| Class Label | 2 5F Gases. 2.1 |
| IMDG | |
| | |
| Class | 2.1 |
| Label | 2.1 |
| ΙΑΤΑ | |
| | |
| Class | 2.1 |
| Label | 2.1 |

according to (EU) 2015/830

Printing date 22.12.2015

Version number 1

Revision: 22.12.2015

Trade name: SILICONE SPRAY

| | (Contd. of page 2 |
|---|--|
| 14.4 Packing group ADR,ADN, IMDG, IATA | Void |
| 14.5 Environmental hazards: Marine pollutant: Special marking (ADR/ADN): | Product contains environmentally hazardou substances: Naphtha (petroleum) hydrotreated light Yes Symbol (fish and tree) Symbol (fish and tree) |
| 14.6 Special precautions for user Danger code (Kemler): EMS Number: Stowage Code Segregation Code | Warning: Gases. - F-D,S-U SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. Fo AEROSOLS with a capacity above 1 litre Category B. For WASTE AEROSOLS Category C, Clear of living quarters. SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9 Stow "separated from" class 1 except fo division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. Fo WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2. |
| 14.7 Transport in bulk according to Ann II of Marpol and the IBC Code | Not applicable. |
| Transport/Additional information: | |
| ADR/ADN Limited quantities (LQ) Excepted quantities (EQ) Transport category Tunnel restriction code | 1L Code: E0 Not permitted as Excepted Quantity 2 D |
| | υ |
| IMDG Limited quantities (LQ) Excepted quantities (EQ) | 1L Code: E0 Not permitted as Excepted Quantity |
| UN "Model Regulation": | UN 1950 AEROSOLS, 2.1 ENVIRONMENTALLY HAZARDOUS |

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

(Contd. on page 9)

Printing date 22.12.2015

Version number 1

Revision: 22.12.2015

(Contd. of page 8)

Trade name: SILICONE SPRAY

Seveso category

P3a FLAMMABLE AEROSOLS

E2 Hazardous to the Aquatic Environment

 \cdot Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t

· Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

· 15.2 Chemical safety assessment:

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.
H224 Extremely flammable liquid and vapour.
H225 Highly flammable liquid and vapour.
H280 Contains gas under pressure; may explode if heated.
H304 May be fatal if swallowed and enters airways.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.
Department issuing MSDS: Abteilung Produktsicherheit

• Abbreviations and acronyms:

Flam. Gas 1: Flammable gases, Hazard Category 1 Aerosol 1: Flammable aerosols, Hazard Category 1 Press. Gas C: Gases under pressure: Compressed gas Flam. Liq. 1: Flammable liquids, Hazard Category 1 Flam. Liq. 2: Flammable liquids, Hazard Category 2 STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3 Asp. Tox. 1: Aspiration hazard, Hazard Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2